



SPARE KEY FOR KEYSWITCH MOBILE PANEL,
ARRANGED IN PAIRS WITH KEY RING AMOUNT AND
CONTENT: SEE TECHNICAL DATA

Standards, approvals, certificates	
CE mark	Yes
Ambient conditions	
Operating temperature	
Operating temperature range, min.	0 °C
Operating temperature range, max.	55 °C
Storage/transport temperature	
min.	-20 °C
max.	70 °C
Relative humidity	
Operation, max.	90 %
Mechanics/material	
Sheet steel	Yes ; Handle made of plastic
Dimensions	
Width	35 mm
Height	18 mm
Thickness	4 mm
Weights	

Weight without packaging	30 g
Scope of supply	
Delivery unit in items	10 ; Coupled with key ring
Other	
Note:	For all Mobile Panels with key-operated switch
Usable in the following products	
Product 1	6AV6645-0DE01-0AX1
Product 2	6AV6645-0EC01-0AX1
Product 3	6AV6645-0EF01-0AX1
Product 4	6AV6645-0FE01-0AX1
Product 5	6AV6645-0GC01-0AX1
Product 6	6AV6645-0GF01-0AX1
Product 7	6AV6645-0CC01-0AX0
Product 8	6AV6645-0AC01-0AX0
Product 9	6AV6645-0BC01-0AX0
Status	Jul 21, 2014