

SIEMENS

Product data sheet

6AV6645-0DE01-0AX1



SIMATIC MOBILE PANEL 277 IWLAN V2,
WITH HANDWHEEL,
KEY SWITCH AND TWO ILLUMINATED
PUSHBUTTON,
CONFIGURABLE W. WINCC FLEXIBLE STANDARD
VERSION 2008 AND HIGHER INCL. 1 MAIN
BATTERY POWER SUPPLY TO BE ORDERED
SEPARATELY: 6AV6671-5CE00-0AX1 CHARGING
ST. 6AV6671-5CN00-0AX2 EXTERNAL POWER
SUPPLY UNIT (EU/US/UK/JP)

General information

Customer-specific configuration	Yes
---------------------------------	-----

Display

Design of display	TFT
Screen diagonal	7.5 in
Size	7.5"
Display type	TFT, 65536 colors
Color type	Colors

Resolution (pixels)

Horizontal image resolution	640
Vertical image resolution	480
Resolution (WxH in pixel)	640 x 480

Backlighting

MTBF backlighting (at 25 °C)	about 50,000 hours
------------------------------	--------------------

Control elements

Operating mode	
Operating options	Keys and Touch
Function keys, programmable	18 function keys, 18 with LEDs
Connection for mouse/keyboard/barcode reader	USB / USB / USB
Keyboard fonts	
Keys with LED	Yes
freely inscribable membrane keys	Yes
Number of function keys with LEDs	18
Multi-key operation	Yes
Number of multi-key operations	2
Number of configurable system keys	18
Numeric/alphabetical input	Yes / Yes
Touch operation	
Touch screen	Analog, resistive
Touch screen (analog/resistive)	Yes
Special operator controls	
Illuminated pushbutton	Yes
Handwheel	Yes
Supply voltage	
Supply voltage	DC
Processor	
Processor	ARM, 520 MHz
Processor type	ARM
Memory	
Type	Flash / RAM
Usable memory for user data	6 MB usable memory for user data
Main memory	
Capacity of main memory, maximum	128 Mbyte
Type of output	
Status LEDs	Yes
Power LED	Yes
Time of day	
Clock	

Type	Hardware clock, battery backup, synchronizable
Interfaces	
Interfaces	1 x Ethernet (RJ45)
USB port	1 x USB
Multi Media Card slot	1 MMC/SD card slot
Industrial Ethernet	
Industrial Ethernet interface	1 x Ethernet (RJ45)
Protocols	
Protocols (Ethernet)	
TCP/IP	Yes
EMC	
Emission of radio interference acc. to EN 55 011	
Emission of radio interferences acc. to EN 55 011 (limit class A)	Yes ; The product is designed for use in industrial environments. When used in residential areas, the emission of radio interference according to limit class B of EN 55011 must be ensured. For further information refer to the user documentation
Degree and class of protection	
IP65 enclosure	Yes
Standards, approvals, certificates	
Certifications	CE, cULus, C-TICK
Ambient conditions	
Drop height	1.2 m
Operating temperature	
Operation	0 °C to +40 °C
Storage/transport temperature	
Transport, storage	-20 °C to +60 °C
Relative humidity	
max. relative humidity	80 %
Operating systems	
Operating system	Windows CE
Configuration	
Message indicator	Yes
With alarm logging system (incl. buffer and acknowledgment)	Yes

Process value display (output)	Yes
Process value default (input) possible	Yes
Recipe administration	Yes
Configuration software	
WinCC flexible Standard	Yes
WinCC Advanced (TIA Portal)	Yes ; V11 SP2 or higher
Configuration tool	WinCC flexible Standard Version 2008 SP2 and higher (to be ordered separately)
2nd configuration kit	WinCC flexible Standard
Version	Version 2008 SP2
Configuration tool	WinCC flexible
Type	Standard
Languages	
Online languages	
Number of online/runtime languages	16
Languages	
Languages per project	32
Functionality under WinCC flexible	
Libraries	Yes
Applications/options	Internet Explorer, Sm@rtService, Sm@rtAccess
Number of Visual Basic Scripts	50
Task planner	Yes
Help system	Yes
Number of characters per info text	70
With alarm logging system (incl. buffer and acknowledgment)	
Number of alarm classes	32
Number of messages	4000
Bit messages	Yes
Analog messages	Yes
Number of bit messages	4000
Number of analog messages	4000
System messages HMI	Yes
System messages PLC	Yes
Message length (in characters)	80

Lines	1
Number of process values per message	8
Acknowledgment groups	99
Message indicator	Yes
First/last value	Yes
Recipes	
Number of recipes	300
Data records per recipe	500
Entries per data record	1000
Recipe memory	64 KB integrated Flash, expandable
Variables	
Number of variables per device	2048
Number of variables per screen	200
Number of variables	1000
Initial values	2048
Limit values	Yes
Multiplexing	Yes
Structs	Yes
Type Date & Time	2048
Images	
Number of configurable images	500
Permanent window/default	Yes
Start screen configurable	Yes
Image selection by PLC	Yes
Image number in the PLC	Yes
Image objects	
Text objects	10,000 text elements
Fields per image	200
Date/time fields	200
Return	Yes
Graphics object	Bit maps, icons, vector graphics
Icons	1000
Complex image objects	

Status/control	With SIMATIC S7
dynamic objects	Diagrams, bar graphs, sliders, analog display, invisible buttons
Number of objects per project	1000
Number per image	10
Methods	Trend / profile
Limit value lines	Yes
Number of bars per chart	10
Limit value lines	Yes
alphanumeric fields	300
alphanumeric fields per image	200
numerical fields	2048
numerical fields per image	200
Password errors	2048
Number of slides per image	10
Number of analog indicators per image	10
Number of visible switches per project	200
visible switches per image	200
hidden switches per image	200
Number of status switches per project	200
Button status switches per image	200
Number of selector switches per project	200
Selector switches per image	200
Number of decade switches per project	200
Decade switches per image	200
Number of signal lamps per project	200
Signal lamps per image	200
Attributes for dynamic objects	
Color change	Yes
X/Y movement	Yes
Hide	Yes
Lists	
Number of text lists per project	500
Number of text lists per image	200

Number of entries per text list	256
Number of graphics lists per project	400
Number of graphic lists per image	200
Number of entries per graphics list	256
Archiving	
Number of archives per device	20
Number of measuring points per project	20
Number of entries per archive	10000
Message archive	Yes
Process value archive	Yes
Archiving methods	
Sequential archive	Yes
Short-term archive	Yes
Memory location	Multi Media Card
Data storage format	
CSV	Yes
Online evaluation	
Using trend curves	Yes
Filters	
cyclic	Yes
Tolerance	Yes
Change	Yes
Security	
Number of user groups	50
Number of user rights	32
Password export/import	Yes
Logging through printer	
Recording/Printing	Alarms, report (shift report), PROFINET
Transfer (upload/download)	
Transfer of configuration	USB, Ethernet, automatic transfer recognition
Process coupling	
Connection to controller	S7-200, S7- 300/400 see section on "System interfaces"
S7-200	Yes

Ethernet	Yes
S7-300/400	Yes
PROFINET	Yes
Functions	
TAB sequence	Yes
Calculating functions	Yes
Animate	Yes
Service tools/configuration aids	
Clean screen	Yes
Touch calibration	Yes
Backup/restore	Yes
Simulation	Yes
Device switchover	Yes
Delta transfer	Yes
I/O / Options	
I/O devices	Barcode reader
Multi Media Card	Yes
SD card	Yes
USB memory	Yes
Additional software components loadable	Yes
Mechanics/material	
Type of housing (front)	Plastic
Dimensions	
Housing diameter/depth (mm)	Dia 290 mm / D 103 mm
Weight	
Weight	2.2 kg
other	
free hotline	Yes
Warranty period	1 a
Status	Jul 17, 2012