



Figure similar

SIMATIC MOBILE PANEL 277F IWLAN V2, WITH INTEGRATED ENABLING- EMERGENCY-STOP BUTTON, HANDWHEEL, KEY SWITCH AND TWO ILLUMINATED PUSHBUTTONS, SUPPORTING IPCF (RAPID ROAMING) CONFIGURABLE W. WINCC FLEXIBLE STANDARD WITH VERSION 2008 SP 2 INCL. 1 MAIN BATTERY POWER SUPPLY TO BE ORDERED SEPARATELY: 6AV6671-5CE00-0AX1 CHARGING ST. 6AV6671-5CN00-0AX2 EXTERNAL POWER SUPPLY UNIT (EU/US/UK/JP)

General information	
Customer-specific configuration	Yes
Display	
Design of display	TFT
Screen diagonal	7.5 in
Number of colors	65 536
Color type	Colors
Resolution (pixels)	
• Resolution (WxH in pixel)	640 x 480
• Horizontal image resolution	640 Pixel
• Vertical image resolution	480 Pixel
Backlighting	
• MTBF backlighting (at 25 °C)	50 000 h
Control elements	
Control elements	Keys and Touch
Keyboard fonts	

• Membrane keyboard — user-definable label membrane keys • Function keys — Number of function keys — Number of function keys with LEDs • Keys with LED • Numeric/alphabetical input • Multi-key operation — Number of multi-key operations	Yes 18 18 Yes Yes / Yes Yes 2
Touch operation	
• Design as touch screen	Yes; analog, resistive
Connection type	
• Connection for mouse/keyboard/barcode reader	USB / USB / USB
Special operator controls	
• Emergency stop button (forced blocking) • Acknowledgement button • Key-operated switch • Illuminated pushbutton • Handwheel	Yes Yes No No No
Supply voltage	
Type of supply voltage	DC
Processor	
Processor type	ARM, 520 MHz
Memory	
Type of memory	Flash / RAM
Memory available for user data	6 Mbyte
Main memory • Capacity of main memory, max.	128 Mbyte
Type of output	
Status LEDs	Yes
Power LED	Yes
Time of day	
Clock	
• Type • Hardware clock (real-time) • retentive • synchronizable	Hardware clock, battery backup, synchronizable Yes Yes Yes
Interfaces	
Interfaces/bus type	1 x Ethernet (RJ45)

Number of RS 485 interfaces	0
Number of USB interfaces	1
USB port	1 x USB
Multimedia Card slot	1 MMC/SD card slot
Industrial Ethernet	
• Industrial Ethernet interface	1 x Ethernet (RJ45)
Protocols	
PROFINET	Yes
Supports protocol for PROFINET IO	Yes
PROFIsafe	Yes
PROFIBUS	No
Protocols (Ethernet)	
• TCP/IP	Yes
Further protocols	
• MODBUS	No
• other bus systems	No
EMC	
Emission of radio interference acc. to EN 55 011	
• Limit class A, for use in industrial areas	Yes; The product is designed for use in industrial environments. When used in residential areas, the emission of radio interference according to limit class B of EN 55011 must be ensured. For further information refer to the user documentation
Degree and class of protection	
Enclosure according to EN 60529	IP65
Standards, approvals, certificates	
Certifications	CE, cULus, C-TICK
CE mark	Yes
cULus	Yes
RCM (formerly C-TICK)	Yes
TÜV safety certification	Yes
Highest safety class achievable in safety mode	
• Performance level according to EN ISO 13849-1:2008	e
• SIL acc. to IEC 61508	SIL 3
Ambient conditions	
Free fall	
• Fall height, max.	1.2 m
Ambient temperature during operation	
• min.	0 °C
• max.	40 °C
Ambient temperature during storage/transportation	

• min.	-20 °C
• max.	60 °C
Relative humidity	
• Operation, max.	80 %
Operating systems	
Operating system	Windows CE
Configuration	
Message indicator	Yes
Alarm logging system (incl. buffer and acknowledgment)	Yes
Process value display (output)	Yes
Process value default (input) possible	Yes
Recipe management	Yes
Configuration software	
• WinCC flexible Compact	No
• WinCC flexible Standard	Yes
• WinCC flexible Advanced	No
• WinCC Basic (TIA Portal)	No
• WinCC Comfort (TIA Portal)	Yes; V11 SP2 or higher
• WinCC Advanced (TIA Portal)	Yes; V11 SP2 or higher
• WinCC Professional (TIA Portal)	Yes; V11 SP2 or higher
• Configuration tool	WinCC flexible Standard Version 2008 SP2 and higher (to be ordered separately)
• 2. Configuration kit	WinCC flexible Standard
— Version	Version 2008 SP2
— Configuration tool	WinCC flexible
— Type	Standard
Languages	
Online languages	
• Number of online/runtime languages	16
Project languages	
• Languages per project	32
Functionality under WinCC (TIA Portal)	
Libraries	Yes
Applications/options	Internet Explorer, Sm@rtService, Sm@rtAccess
Number of Visual Basic Scripts	Yes
Task planner	Yes
Help system	Yes
• Number of characters per info text	70
Message system	
• Number of alarm classes	32

• Number of messages	4 000
• Bit messages	Yes
— Number of bit messages	4 000
• Analog messages	Yes
— Number of analog messages	4 000
• System messages HMI	Yes
• System messages PLC	Yes
• Lines	1
• Number of characters per message	80
• Number of process values per message	8
• Acknowledgment groups	
— Number of acknowledgement groups	99
• Message indicator	Yes
• First/last value	Yes
Recipe management	
• Number of recipes	300
• Data records per recipe	500
• Entries per data record	1 000
• Recipe memory	64 KB integrated Flash, expandable
Variables	
• Number of variables per device	2 048
• Number of variables per screen	200
• Number of variables	1 000
• Initial values	2 048
• Type Date & Time	2 048
• Limit values	Yes
• Multiplexing	Yes
• Structures	Yes
Images	
• Number of configurable images	500
• Permanent window/default	Yes
• Start screen configurable	Yes
• Image selection by PLC	Yes
• Image number in the PLC	Yes
Image objects	
• Text objects	10,000 text elements
• Number of I/O fields per image	200
• Number of date/time fields	200
• Return	Yes
• Graphics object	Bit maps, icons, vector graphics
— Icons	1 000

Complex image objects	
• Status/control	Yes; With SIMATIC S7
• dynamic objects	Diagrams, bar graphs, sliders, analog display, invisible buttons
— Number of objects per project	1 000
— Number of curve diagrams per image	10
• Methods	Trend / profile
• Bar graphs	
— Number of bars per chart	10
• Sliders	
— Number of slides per image	10
• Pointer instruments	
— Number of analog indicators per image	10
• Limit value lines	Yes
• Number of alphanumerical fields	300
— alphanumeric fields per image	200
• Number of numerical fields	2 048
— numerical fields per image	200
• Number of password fields	2 048
• Number of visible switches per project	200
— visible switches per image	200
— hidden switches per image	200
• Number of status switches per project	200
— Number of status switches per image	200
• Number of selector switches per project	200
— Selector switches per image	200
• Number of decade switches per project	200
— Decade switches per image	200
• Number of signal lamps per project	200
— Signal lamps per image	200
Attributes for dynamic objects	
• Color change	Yes
• X/Y movement	Yes
• Hide	Yes
Lists	
• Number of text lists per project	500
• Number of text lists per image	200
• Number of entries per text list	256
• Number of graphics lists per project	400
• Number of graphic lists per image	200
• Number of entries per graphics list	256
Archiving	

• Number of archives per device	20
• Number of measuring points per project	20
• Number of entries per archive	10 000
• Message archive	Yes
• Process value archive	Yes
• Archiving methods	
— Sequential archive	Yes
— Short-term archive	Yes
• Memory location	MultiMediaCard
• Data storage format	
— CSV	Yes
• Online evaluation	
— using trend curves	Yes
Filters	
• cyclic	Yes
• Tolerance	Yes
• Change	Yes
Security	
• Number of user groups	50
• Number of user rights	32
• Password export/import	Yes
Logging through printer	
• Recording/Printing	Alarms, report (shift report), PROFINET
Transfer (upload/download)	
• Transfer of configuration	USB, Ethernet, automatic transfer recognition
Process coupling	
• Connection to controller	S7-200, S7- 300/400 see section on "System interfaces"
• S7-1200	Yes
• S7-1500	Yes; As of V13 SP1 Update 4, PROFINET communication also possible
• S7-200	Yes
— Ethernet	Yes
• S7-300/400	Yes
— PROFINET	Yes
• SIMOTION	Yes; WinCC flexible 2008 SP3 or higher
Functions	
• TAB sequence	Yes
• Calculating functions	Yes
• Animate	Yes
Service tools/configuration aids	
• Clean screen	Yes
• Touch calibration	Yes

- Backup/Restore manually
- Simulation
- Device switchover
- Delta transfer

Yes
Yes
Yes
Yes

Peripherals/Options

Peripherals

- SIMATIC HMI MM memory card: Multi Media Card
- SIMATIC HMI SD memory card: Secure Digital memory card
- USB memory

Barcode reader

Yes
Yes
Yes

Additional software components loadable

Yes

Mechanics/material

Type of housing (front)

plastic

Dimensions

Enclosure diameter

290 mm

Depth of housing

103 mm

Weights

Weight (without packaging)

2.2 kg

Other

free hotline

Yes

Warranty period

1 y

last modified:

08/16/2016