

STARTER PACKAGE 277 IWLAN V2, COMPRISING: MOBILE
PANEL 277 IWLAN V2 WITH HANDWHEEL, KEY SWITCH AND
ILLUMINATED PUSHB. UNIT, CHARGING STATION, SPARE
BATTERY WINCC FLEXIBLE 2008 STANDARD,



Figure similar

Display	
Design of display	TFT
Screen diagonal	7.5 in
Number of colors	65 536
Resolution (pixels)	
• Horizontal image resolution	640 Pixel
• Vertical image resolution	480 Pixel
Control elements	
Keyboard fonts	
• Function keys	18
— Number of function keys	
• Keys with LED	Yes
Touch operation	
• Design as touch screen	Yes
Memory	
Memory available for user data	6 Mbyte

Interfaces	
Number of RS 485 interfaces	0
Number of USB interfaces	1
Protocols	
Supports protocol for PROFINET IO	Yes
PROFIsafe	No
PROFIBUS	No
Protocols (Ethernet)	
• TCP/IP	Yes
Further protocols	
• MODBUS	Yes; Modicon (MODBUS TCP/IP)
• other bus systems	Yes; Allen-Bradley E/IP C.Logix
Ambient conditions	
Free fall	
• Fall height, max.	1.2 m
Ambient temperature during operation	
• min.	0 °C
• max.	40 °C
Languages	
Online languages	
• Number of online/runtime languages	16
Functionality under WinCC (TIA Portal)	
Security	
• Number of user groups	50
Weights	
Weight (without packaging)	2.2 kg
last modified:	10/25/2016