

STARTER PACKAGE 277F IWLAN V2, COMPRISING: MOBILE
PANEL 277F IWLAN V2 WITH ENABLING BUTTON, EMERGENCY-
STOP BUTTON, HANDWHEEL, KEY SWITCH AND ILLUMINATED
PUSHB. UNIT, CHARGING STATION, SPARE BATTERY THREE
TRANSPONDERS V3 WINCC FLEXIBLE 2008 STANDARD,



Figure similar

Display	
Design of display	TFT
Screen diagonal	7.5 in
Number of colors	65 536
Resolution (pixels)	
• Horizontal image resolution	640 Pixel
• Vertical image resolution	480 Pixel
Control elements	
Keyboard fonts	
• Function keys	18
— Number of function keys	
• Keys with LED	Yes
Touch operation	
• Design as touch screen	Yes
Memory	
Memory available for user data	6 Mbyte

Interfaces	
Number of RS 485 interfaces	0
Number of USB interfaces	1
Protocols	
Supports protocol for PROFINET IO	Yes
PROFIsafe	Yes
PROFIBUS	No
Protocols (Ethernet)	
• TCP/IP	Yes
Further protocols	
• MODBUS	No
• other bus systems	No
Ambient conditions	
Free fall	
• Fall height, max.	1.2 m
Ambient temperature during operation	
• min.	0 °C
• max.	40 °C
Languages	
Online languages	
• Number of online/runtime languages	16
Functionality under WinCC (TIA Portal)	
Security	
• Number of user groups	50
Weights	
Weight (without packaging)	2.2 kg
last modified:	10/25/2016