

SERVICE SET FOR TP 177MICRO, TP 177A, TP 177B, OP 177B
AMOUNT AND CONTENT: SEE TECHNICAL DATA



General information	
Product type designation	Service set 6" devices, Type 3
Standards, approvals, certificates	
CE mark	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	55 °C
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	70 °C
Relative humidity	
• Operation, max.	95 %
Scope of supply	
Delivery quantity in pieces	
• Parts per unit	1; Content: 1 x mounting seal TP 177, 1 x mounting seal OP 177, 7 x plastic mounting clip, 1 x 2-pin female connector

Other

Target devices

for TP 177micro, TP 177A, TP 177B, OP 177B

Usable in the following products

• Product 1	6AV6640-0CA11-0AX0
• Product 2	6AV6642-0AA11-0AX0
• Product 3	6AV6642-0AA11-0AX1
• Product 4	6AV6642-0BC01-1AX0
• Product 5	6AV6642-0BA01-1AX0
• Product 6	6AV6642-0BD01-3AX0
• Product 7	6AV6642-0BA01-1AX1
• Product 8	6AV6642-0BC01-1AX1
• Product 9	6AV6642-8BA10-0AA0
• Product 10	6AV6642-0DC01-1AX0
• Product 11	6AV6642-0DA01-1AX0
• Product 12	6AV6642-0DC01-1AX1
• Product 13	6AV6642-0DA01-1AX1

last modified:

10/21/2016