

MOBILE PANEL 277(F) IWLAN, SERVICE SET V1 AMOUNT AND
CONTENT: SEE TECHNICAL DATA



General information	
Product type designation	Service set Mobile Panel 277 (F) IWLAN V1
Standards, approvals, certificates	
CE mark	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	55 °C
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	70 °C
Relative humidity	
• Operation, max.	95 %
Scope of supply	
Delivery quantity in pieces	

- Parts per unit

1; Content: 2x covers for charging station l/r, 1x connector for charging station, 2x corner seals l/r, 2x gasket corner seals, 4x decorative film corner seals l/r, 1x backup battery 3.6 V / 1.5 Ah including cover, 1x spare key for charging cradle

Other

Target devices for Mobile Panel 277 IWLAN V1, Mobile Panel 277F IWLAN V1

Usable in the following products

- Product 1 [6AV6645-0DD01-0AX0](#)
- Product 2 [6AV6645-0DE01-0AX0](#)
- Product 3 [6AV6645-0DB01-0AX0](#)
- Product 4 [6AV6645-0DC01-0AX0](#)

last modified:

10/26/2016