

TRANSPONDER V2 F. MOBILE PANEL 277(F) IWLAN V2 NOT
APPLICABLE F. MOBILE PANEL 277(F) IWLAN V1!



Degree and class of protection	
Enclosure according to EN 60529	IP65
Enclosure according to NEMA	NEMA 4x, NEMA 12
Standards, approvals, certificates	
Certifications	CE, cULus, C-TICK, NEMA 4x, NEMA 12
CE mark	Yes
cULus	Yes
RCM (formerly C-TICK)	Yes
Ambient conditions	
Ambient temperature during operation	
• Operation (vertical installation)	0 to +50 °C
— For vertical installation, min.	0 °C
— For vertical installation, max.	50 °C
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	60 °C
Relative humidity	
• Operation, max.	85 %

Dimensions	
Width	172 mm
Height	90 mm
Depth	38.5 mm

Weights	
Weight (without packaging)	0.3 kg

Other	
Usable in the following products	
• Product 1	6AV6645-0DD01-0AX1
• Product 2	6AV6645-0DE01-0AX1
• Product 3	6AV6645-0EB01-0AX1
• Product 4	6AV6645-0EC01-0AX1
• Product 5	6AV6645-0FD01-0AX1
• Product 6	6AV6645-0FE01-0AX1
• Product 7	6AV6645-0GB01-0AX1
• Product 8	6AV6645-0GC01-0AX1

last modified: 10/08/2016