



ALUMINUM MOUNTING CLIP FOR BASIC PANEL 1ST GENERATION 4" AND LARGER NOT 4" COLOR, COMFORT PANEL 7 TO 12", TP 177 4", TP/OP 277 6", MP177, MP 277, MP 377, THIN CLIENT, IPC277D 7 TO 12", SHEET THICKNESS 4 TO 6 MM AMOUNT: SEE TECHNICAL DATA

Installation type/mounting	
Mounting in portrait format possible	Yes
Mounting in landscape format possible	Yes
Standards, approvals, certificates	
CE mark	Yes
Ambient conditions	
Operating temperature	
Operating temperature range, min.	0 °C
Operating temperature range, max.	55 °C
Storage/transport temperature	
min.	-20 °C
max.	70 °C
Relative humidity	
Operation, max.	90 %
Mechanics/material	
Screw type	
4.5 V	Yes
Type of housing (front)	

Aluminum	Yes
Dimensions	
Width	15 mm
Height	21 mm ; Without screw
Thickness	15 mm
Weights	
Weight without packaging	5 g ; Per unit
Scope of supply	
Delivery unit in items	20
Other	
Note:	TP177-4", TP/OP 277-6", MP177-6, MP277-10" T, MP277-8", MP277-8"T, MP277-10"K, MP377 12-19", TC 10", TC 15", KTP400 Basic mono, KTP600, KTP1000, KTP1500, KP700 Comfort, TP700 Comfort, KP900 Comfort, TP900 Comfort, KP1200 Comfort, TP1200 Comfort and IPC 277D 7, 9, 12"
Usable in the following products	
Product 1	6AV6642-0BD01-3AX0
Product 2	6AV6643-0AA01-1AX0
Product 3	6AV6643-0BA01-1AX0
Product 4	6AV6643-7BA00-*
Product 5	6AV6642-0EA01-3AX0
Product 6	6AV6643-0D*
Product 7	6AV6643-0C*
Product 8	6AV6643-0ED01-2AX0
Product 9	6AV6643-7CD00*
Product 10	6AV6643-7DD00-*
Product 11	6AV6644-*
Product 12	6AV6647-0AA11-3AX0
Product 13	6AV6647-0AB11-3AX0
Product 14	6AV6647-0AC11-3AX0
Product 15	6AV6647-0AD11-3AX0
Product 16	6AV6647-0AE11-3AX0
Product 17	6AV6647-0AF11-3AX0
Product 18	6AV2124-1GC01-0AX0
Product 19	6AV2124-0GC01-0AX0
Product 20	6AV2124-1JC01-0AX0
Status	Aug 7, 2014