SIEMENS

Data sheet

6AV6676-6MB10-0AX0

SIMATIC MODBUS/TCP PN RED FOR S7-400 PN-(H) SYSTEMS, SINGLE LICENSE, ON CD



General information	
Engineering with	
 STEP 7 TIA Portal configurable/integrated as of version 	V11
 STEP 7 configurable/integrated as of version 	As of STEP7 V5.5
 PCS 7 configurable/integrated as of version 	PCS 7 V7.1 SP2
Redundancy	
Redundancy capability	Yes; Suitable for configuring H systems
Protocols	
SIMATIC communication	
 Communication as Modbus server 	Yes
 Communication as Modbus client 	Yes
 User data per job (of which consistent), max. 	250 byte
Software	
Runtime software	
Target system	
— ET 200S	Yes
— S7-300	Yes

C7 400	Yes
— S7-400	Yes
— WinAC Block	165
	196 h. to
Local data requirements	186 byte
• FB length in RAM, max.	29 kbyte
Multi-instance capable	Yes
Communication data	
 Multiport 	Yes
Master-slave coupling	SIMATIC S7 as master or slave
 implemented function codes 	01, 02, 03, 04, 05, 06, 15, 16
Authorization/licenses	
• Single license (EL)	Yes
Configuration	
Configuration software	
 Wizard for configuration support 	Yes; Wizard
Programming	
Programming language	
— LAD	Yes
— FBD	Yes
— STL	Yes
— SCL	Yes
— CFC	Yes
— GRAPH	Yes
Configuration examples	
— STL example project	Yes
 CFC example project 	Yes
Documentation	
Languages	
	Yes; Electronic, included on CD
German	. 66, 2.668.6786, 8.768.668.61
GermanEnglish	Yes; Electronic, included on CD