SIEMENS

Data sheet

6AV6676-6MB30-3AX0

SIMATIC Modbus/TCP CP RED for S7-400 H systems, Single license on DVD

General information		
Engineering with		
STEP 7 TIA Portal configurable/integrated as of	V11	
version		
 STEP 7 configurable/integrated as of version 	From STEP 7 V5.4 and higher	
 PCS 7 configurable/integrated as of version 	PCS 7 V7.0	
Redundancy		
 Redundancy capability 	Yes; Suitable for configuring H systems	
Protocols		
SIMATIC communication		
Communication as Modbus server	Yes	
 Communication as Modbus client 	Yes	
User data per job (of which consistent), max.	250 byte	
Software		
Runtime software		
Target system		
— ET 200S	Yes	
— S7-300	Yes	
— S7-400	Yes	
— WinAC	No	
Block		
Local data requirements	302 byte	
FB length in RAM, max.	24 kbyte	
Multi-instance capable	Yes	
Communication data		
Multiport	Yes; Dependent on CP	
Master-slave coupling	SIMATIC S7 as master or slave	
 implemented function codes 	01, 02, 03, 04, 05, 06, 15, 16	
Authorization/licenses		
• Single license (EL)	Yes	
Configuration		
Configuration software		

Programming

• Wizard for configuration support

Yes; Wizard

Programming language	
— LAD	Yes
— FBD	Yes
— STL	Yes
— SCL	Yes
— CFC	Yes
— GRAPH	Yes
Configuration examples	
— STL example project	Yes
 CFC example project 	Yes

Documentation

Languages

• German Yes; Electronic, included on CD

• English Yes; Electronic, included on CD

last modified: 12/12/2016