SIEMENS

Data sheet

6AV6676-6MB30-4AX0

SIMATIC Modbus/TCP Red for S7-400 H systems, Single license on CD $\,$



General information	
Engineering with	
 STEP 7 TIA Portal configurable/integrated as of version 	V11
 STEP 7 configurable/integrated as of version 	STEP 7 V5.5 or higher
 PCS 7 configurable/integrated as of version 	PCS 7 V7.1 SP2
Redundancy	
 Redundancy capability 	Yes; Suitable for configuring H systems
Protocols SIMATIC communication	
SIMATIC communication	Vaa
 Communication as Modbus server 	Yes
 Communication as Modbus client 	Yes
 User data per job (of which consistent), max. 	250 byte
Operating systems	
Runs under operating system	
Windows XP	Yes
Windows 7	Yes

Software	
Runtime software	
Target system	
— ET 200S	Yes; FW V3.2 or higher
— S7-300	Yes; FW V3.2 or higher
— S7-400	Yes; FW V6.0 or higher
— WinAC	No
— Suitable for other target system	Yes; See: https://support.industry.siemens.com/cs/ww/en/view/104946406
Block	
Local data requirements	344 byte
 FB length in RAM, max. 	22 kbyte
Multi-instance capable	Yes
Communication data	
Multiport	Yes; Dependent on CP
 implemented function codes 	01, 02, 03, 04, 05, 06, 15, 16
Authorization/licenses	
Single license (EL)	Yes
Configuration	
Configuration software	
Wizard for configuration support	Yes; Wizard
Programming	
Programming language	
— LAD	Yes
— FBD	Yes
— STL	Yes
— SCL	Yes
— CFC	Yes
— GRAPH	Yes
Configuration examples	
— STL example project	Yes
— CFC example project	Yes
Documentation	
Languages	
German	Yes; Electronic, included on CD
English	Yes; Electronic, included on CD
last modified:	07/18/2019