SIEMENS

Data sheet

6AV6881-0AD56-3CA0

Flange mount adapter VESA 100/75, INOX, IP65 for PRO devices. additional information, amount and content: see technical data $\frac{1}{2}$



General information		
Product type designation	VESA 100/75 flange mount IP65	
Installation type/mounting		
Mounting	VESA 100 mm / 75 mm with M6 thread	
Mounting type	Support arm with VESA 100 mm or 75 mm	
Degree and class of protection		
IP (at the front)	IP65	
Standards, approvals, certificates		
Use in hazardous areas		
ATEX Zone 2	No	
ATEX Zone 22	No	
 ATEX as target device 	No	
• IECEx Zone 1	No	
• IECEx Zone 11	No	
• IECEx Zone 2	No	
• IECEx Zone 22	No	
• cULus Class I Zone 1	No	
 cULus Class I Zone 2, Division 2 	No	
 cULus Class II Division 2 	No	
FM Class I Division 2	No	
FM Class II Division 2	No	
Marine approval		
Germanischer Lloyd (GL)	No	
 American Bureau of Shipping (ABS) 	No	
Bureau Veritas (BV)	No	
 Det Norske Veritas (DNV) 	No	
 Korean Register of Shipping (KRS) 	No	
 Lloyds Register of Shipping (LRS) 	No	
 Nippon Kaiji Kyokai (Class NK) 	No	
 Polski Rejestr Statkow (PRS) 	No	
 Chinese Classification Society (CCS) 	No	
Marine approval as target device	No	
Ambient conditions		
Suited for indoor use	Yes	
Suited for outdoor use	No	
Ambient temperature during operation		
• min.	0 °C	
• max.	55 °C	
Ambient temperature during storage/transportation		
• min.	-20 °C	

• max.	70 °C	
Relative humidity		
 Operation, max. 	90 %	
 Condensation permissible 	No	
Mechanics/material		
Material		
Stainless steel	Yes; Stainless steel V2A	
Dimensions		
Width	135 mm; VESA 100/75 PRO INOX adapter	
Height	120 mm; VESA 100/75 PRO INOX adapter	
Depth	67.5 mm; VESA 100/75 PRO INOX adapter	
Scope of supply		
Delivery quantity in pieces	2; 1x VESA INOX IP65 adapter and 1x INOX cable entry INOX IP65 with ICOTEK 3-fach cable entry 6 mm	
Components included	Without additional accessories	
Other		
Merchandise	Yes; VESA 100/75 PRO INOX adapter set IP65	
Manufacturer name	QUERUM products UG	
Manufacturer's address	Wirtsstr. 23, 85110 Kipfenberg-Böhming, Germany	
Target devices	Not suitable for 19" 4:3 devices	
Note:	Max. load 35 kg, for expandable support arm mounting	
Usable in the following products		
• Product 1	6AV2124-*	
Product 2	6AV7251-*	
Product 3	6AV6646-1BD*	
Product 4	6AV7863*	
• Product 5	6AV7250-*	

last modified: 1/25/2024 **C**