

SIMATIC IPC PX-39A 19" multi-touch (1920 x 1080); Intel(R) UHD graphics onboard 4 x USB 3.2 Ethernet (10/100/1000); PCIe (optional); Intel Xeon W-11155MLE (1.8/3.1 GHz, 4C/8T); 8 GB; 1st mass storage: M.2 SSD 256 GB Eco; without 2nd mass storage; Windows 10 IoT Enterprise 2021 LTSC for Celeron, Xeon W-11155MLE, Xeon W-11555MLE; with 1 x Com (RS232/485/422); USB restore stick with D&D and software image (if selected) 24 V DC industrial power supply (power failure, isolated, bridging time);

Display	
Design of display	19" TFT multi-touch
Screen diagonal	18.5 in
Resolution (pixels)	
• Horizontal image resolution	1 920 pixel
• Vertical image resolution	1 080 pixel
Backlighting	
• MTBF backlighting (at 25 °C)	50 000 h
Control elements	
Input device	
• Mouse, at front	No
Keyboard fonts	
• Function keys	No
• alphanumeric keyboard	No
Touch operation	
• Design as multi-touch screen	Yes; Projective-capacitive
Installation type/mounting	
central design	Yes
distributed design	No
Mounting in portrait format possible	Yes
Power loss	
In full configuration	24 V DC: max. 82 W, 110 ... 230 V AC
Dimensions	
Width of the housing front	464 mm
Height of housing front	294 mm
Mounting cutout, width	448 mm
Mounting cutout, height	278 mm
Overall depth	76 mm
Weights	
Weight, approx.	6.6 kg

last modified:

11/29/2023 