

SIMATIC IPC PX-39A 22" multi-touch (1920 x 1080); Intel(R) UHD graphics onboard 4 x USB 3.2 Ethernet (10/100/1000); PCIe (optional); Intel Xeon W-11155MLE (1.8/3.1 GHz, 4C/8T); 16 GB; 1st mass storage: M.2 SSD 512 GB Eco; without 2nd mass storage; without operating system without option 1; restore stick image with D&D and software image (if selected) only via OSD (online portal) 24 V DC industrial power supply (power failure, isolated, bridging time);

| Display                              |                                      |
|--------------------------------------|--------------------------------------|
| Design of display                    | 22" TFT multi-touch                  |
| Screen diagonal                      | 21.5 in                              |
| Resolution (pixels)                  |                                      |
| • Horizontal image resolution        | 1 920 pixel                          |
| • Vertical image resolution          | 1 080 pixel                          |
| Backlighting                         |                                      |
| • MTBF backlighting (at 25 °C)       | 30 000 h                             |
| Control elements                     |                                      |
| Input device                         |                                      |
| • Mouse, at front                    | No                                   |
| Keyboard fonts                       |                                      |
| • Function keys                      | No                                   |
| • alphanumeric keyboard              | No                                   |
| Touch operation                      |                                      |
| • Design as multi-touch screen       | Yes; Projective-capacitive           |
| Installation type/mounting           |                                      |
| central design                       | Yes                                  |
| distributed design                   | No                                   |
| Mounting in portrait format possible | Yes                                  |
| Power loss                           |                                      |
| In full configuration                | 24 V DC: max. 88 W, 110 ... 230 V AC |
| Dimensions                           |                                      |
| Width of the housing front           | 529 mm                               |
| Height of housing front              | 331 mm                               |
| Mounting cutout, width               | 513 mm                               |
| Mounting cutout, height              | 315 mm                               |
| Overall depth                        | 76 mm                                |
| Weights                              |                                      |
| Weight, approx.                      | 7.9 kg                               |

last modified: 5/3/2024 