

SIMATIC IPC PX-39A 24" multi-touch (1920 x 1080); Intel(R) UHD graphics onboard 4 x USB 3.2 Ethernet (10/100/1000); PCIe (optional); Intel Xeon W-11155MLE (1.8/3.1 GHz, 4C/8T); 16 GB; M.2 SSD 512 GB Eco; without 2nd mass storage; Windows 10 IoT Enterprise 2021 LTSC for Celeron, Xeon W-11155MLE, Xeon W-11555MLE; without option 1; restore stick image with D&D and software image (if selected) only via OSD (online portal) 110/230 V AC industrial power supply unit with NAMUR; without power supply cord;

Display	
Design of display	24" TFT multi-touch
Screen diagonal	23.8 in
Resolution (pixels)	
• Horizontal image resolution	1 920 pixel
• Vertical image resolution	1 080 pixel
Backlighting	
• MTBF backlighting (at 25 °C)	30 000 h
Control elements	
Input device	
• Mouse, at front	No
Keyboard fonts	
• Function keys	No
• alphanumeric keyboard	No
Touch operation	
• Design as multi-touch screen	Yes; Projective-capacitive
Installation type/mounting	
central design	Yes
distributed design	No
Mounting in portrait format possible	Yes
Power loss	
In full configuration	24 V DC: max. 88 W, 110 ... 230 V AC
Dimensions	
Width of the housing front	585 mm
Height of housing front	361 mm
Mounting cutout, width	569 mm
Mounting cutout, height	347 mm
Overall depth	91.6 mm
overall depth with depth with PCI expansion	117 mm
Weights	
Weight, approx.	11 kg
Approvals / Certificates	
General Product Approval	



EG-Konf.



[Miscellaneous](#)



UL



RCM

[BIS CRS](#)

General Product Approval

For use in hazardous locations

Maritime application

[KC](#)



ATEX



IECEX

[Type Examination Certificate](#)



ABS



BUREAU VERITAS



[NK / Nippon Kaiji Ky-  
okai](#)

[CCS \(China Classifica-  
tion Society\)](#)



[Dangerous goods in-  
formation](#)

last modified:

3/14/2025