

SIMATIC IPC PX-32A 12" Singletouch 4 x USB 3.2 (back), Ethernet (10/100/1000)
Intel Xeon W-11865MLE (1.5/4.5 GHz, 8C/16T); 32 GB; M.2 SSD 512 GB Eco;
without 2nd mass storage; without operating system without option 1 restore stick
image with D&D and software image (if selected) only via OSD (online portal) 9-36
V DC industrial power supply (wide range)

Display	
Design of display	12" TFT touch
Screen diagonal	12.1 in
Resolution (pixels)	
• Horizontal image resolution	1 280 pixel
• Vertical image resolution	800 pixel
Backlighting	
• MTBF backlighting (at 25 °C)	50 000 h
Control elements	
Input device	
• Mouse, at front	No
Keyboard fonts	
• Function keys	No
• alphanumeric keyboard	No
Touch operation	
• Design as touch screen	Yes
Installation type/mounting	
central design	Yes
distributed design	No
Mounting in portrait format possible	No
Power loss	
In full configuration	83 W
Dimensions	
Width of the housing front	320 mm
Height of housing front	226 mm
Mounting cutout, width	302 mm
Mounting cutout, height	208 mm
Overall depth	89 mm
Weights	
Weight, approx.	4.5 kg
Approvals / Certificates	
General Product Approval	



General Product Ap- proval	Dangerous goods
KC	Dangerous goods in- formation