

SIMATIC IPC PX-32A 15" ST Singletouch 4 x USB 3.2 (back), Ethernet (10/100/1000) Intel Xeon W-11865MLE (1.5/4.5 GHz, 8C/16T); 32 GB; without 1st mass storage; without 2nd mass storage; without operating system without option 1 USB restore stick with D&D and software image (if selected) 9-36 V DC industrial power supply (wide range)

Display	
Design of display	15" TFT touch
Screen diagonal	15.6 in
Resolution (pixels)	
• Horizontal image resolution	1 366 pixel
• Vertical image resolution	768 pixel
Backlighting	
• MTBF backlighting (at 25 °C)	50 000 h
Control elements	
Input device	
• Mouse, at front	No
Keyboard fonts	
• Function keys	No
• alphanumeric keyboard	No
Touch operation	
• Design as touch screen	Yes
Installation type/mounting	
central design	Yes
distributed design	No
Mounting in portrait format possible	No
Power loss	
In full configuration	83 W
Dimensions	
Width of the housing front	406 mm
Height of housing front	258 mm
Mounting cutout, width	388.4 mm
Mounting cutout, height	240.5 mm
Overall depth	96 mm
Weights	
Weight, approx.	6 kg
Approvals / Certificates	
General Product Approval	



General Product Approval	Dangerous goods
KC	Dangerous goods information