

IP65 STAINLESS STEEL KEYBOARD MOUNTABLE AT SIMATIC
HMI PRO UNITS, WITH NUMBER PAD, LAYOUT: US
ADJUSTABLE INCLINATION WIDTH: 483MM (19" PRO UNIT)



General information

Product type designation	USB-INOX keyboard PRO, mouse keys
--------------------------	-----------------------------------

Control elements

Keyboard fonts

• Design	Keyboard with short-stroke keys
• Keyboard assignment	English
• Color of the buttons	Stainless steel
• Color of the key inscription	Black
• Key illumination	No
• Function keys	
— Number of function keys	12
• Number pad	Yes; Free-standing
• Status LED displays	Yes; Num, Caps and Scroll
— for number pad	Yes
— for Shift keys	Yes

Touch operation

• Integrated touch pad	No; Cursor control possible, left and right mouse button
------------------------	--

Connection type

• Bluetooth radio standard	No
• USB	Yes; Type A
• PS/2	No
• Cable length	1.5 m
Frame size/design	
• Standard	Yes; For industrial applications
Installation type/mounting	
Rack mounting possible	No
Wall mounting/direct mounting possible	Yes; Support arm mounting
maximum permissible angle of inclination without external ventilation	90°; Between 90° and 180° in steps of 15°
Supply voltage	
Type of supply voltage	via USB
Input current	
Current consumption (rated value)	100 mA; Typical
Battery	
Battery charge indicator	No; maintenance-free
Degree and class of protection	
IP (at the front)	IP65
Splashproof	Yes
Standards, approvals, certificates	
CE mark	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	60 °C
Ambient temperature during storage/transportation	
• min.	0 °C
• max.	60 °C
Relative humidity	
• Operation, max.	80 %; no condensation
• Condensation permissible	No
Operating systems	
Runs under operating system	
• Windows CE	Yes
• Windows Vista	Yes
• Windows XP	Yes
• Windows 7	Yes
• Windows 8	Yes

Mechanics/material	
Material	
• Stainless steel	Yes; Between 90° and 180° in steps of 15°
Service life	
• Number of operating cycles, keys	10 000 000; Operations (minimum)
Dimensions	
Width	481 mm
Height	20 mm
Depth	171.6 mm
Weights	
Weight without packaging	3 700 g; Without accessories
Weight incl. packaging	5 300 g
Scope of supply	
Delivery quantity in pieces	1; With support arm bracket
Other	
Target devices	Suitable for IPC and HMI devices with the corresponding interfaces (see manual)
Note:	Customer-specific information see Siemens supplement A5E02963817B; TP1500 Comfort Outdoor / TP700 Comfort Outdoor: Observe the temperature range
Usable in the following products	
• Product 1	6AV2124-0GC13-0AX0
• Product 2	6AV2124-0QC13-0AX0
last modified:	10/15/2016