

Extension unit 15" hardwired for mounting on all fully IP65-enclosed 16:9 HMI/IPC devices. For the flexible installation of operator controls, 8 mounting positions, 8 operator controls equippable; connection via hardwired connection (without equipment)



General information

Product type designation	Extension Unit 15" hardwired
--------------------------	------------------------------

Control elements

Connection type

• Connection type of the LED module	12-pin connector
• Connection type of the contacts of the control elements	16-pin connector
• Connection type of the safety-related contacts (emergency stop)	8-pin connector

Installation type/mounting

Mounting	For mounting on a 16:9 HMI / IPC PRO device (lower part)
Mounting type	Screwed joint
Rack mounting	No
Front mounting	No
Number of slots for command devices and signaling units	8

Supply voltage

Type of supply voltage	DC
------------------------	----

Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption (rated value)	10 mA; without load
Output current	
per output	500 mA; max.
Power	
Active power input, typ.	0.1 W
Emitted active power	5 W
Degree and class of protection	
IP65 (all-round)	Yes
Enclosure Type 4 at the front	Yes
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes
cULus	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
Suitable for safety functions	Yes; e.g. installation of emergency stop
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	50 °C
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	60 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	2 000 m
Relative humidity	
• Operation, max.	90 %; no condensation
Cables	
Cable length	30 m
Mechanics/material	
Material	
• Aluminum	Yes
Enclosure material (front)	
• Aluminum	Yes; Knockout covered with black film
Dimensions	

Width	396 mm
Height	99 mm
Thickness	100.65 mm

Weights

Weight without packaging	2.5 kg
--------------------------	--------

Scope of supply

Delivery quantity in pieces	1
Components included	All connectors required for customer interfaces

last modified: 08/15/2019