

SIMATIC FLAT PANEL 15T, 15 INCH TOUCH TFT-DISPLAY WITH 1024X768 PIXEL RESOLUTION 24V DC, VGA, DVI-D INTERFACE, INCL. VGA-CABLE 1,8M

General information

Product type designation	Flat panel monitors
--------------------------	---------------------

Display

Design of display	TFT widescreen display, LED backlighting
Screen diagonal	15 in
visible area (HxV) in mm	304 x 228
Viewing angle	100° x 90° (min)
On Screen Display (OSD) configuration	Yes
Number of colors	16 000 000; 16.2 million
Number of colors (bit levels)	16.2 million

Resolution (pixels)

• Resolution (WxH in pixel)	1024 x 768
• Horizontal image resolution	1 024 Pixel
• Vertical image resolution	768 Pixel

General features

• Brightness/contrast	> 260 cd/m ² / 350:1
-----------------------	---------------------------------

Backlighting

• Type of backlighting	LED, dimmable
• MTBF backlighting (up to 50%, at 25 °C)	50 000 h; At 25°C
• Backlight dimmable	Yes; 0-100 %

Control elements

Input device

• Integrated mouse cursor control	No
-----------------------------------	----

Keyboard fonts

• Function keys	No
— Number of function keys	0

Installation type/mounting

Design	Built-in unit
Rack mounting possible	Yes
Built-in unit	Yes; Portrait mode possible
• permissible angle to the vertical backward (console)	70°; max. 40°C
• permissible angle to the vertical forward (ceiling mounting)	35°; max. 40°C

VESA mounting	No
Supply voltage	
Type of supply voltage	AC/DC
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
permissible range, lower limit (AC)	90 V
permissible range, upper limit (AC)	264 V
Interfaces	
Video interfaces	
• analog video signal (VGA)	Yes
Degree and class of protection	
IP54 at front	Yes; For screw mounting in 19" rack
IP65 at front	Yes; if mounted with the supplied latch fasteners
Standards, approvals, certificates	
UL approval	Yes
EAC (formerly Gost-R)	No
Marine approval	
• Germanischer Lloyd (GL)	Yes; Optional
• American Bureau of Shipping (ABS)	Yes; Optional
• Bureau Veritas (BV)	Yes; Optional
• Det Norske Veritas (DNV)	Yes; Optional
• Lloyds Register of Shipping (LRS)	Yes; Optional
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	50 °C
Mechanics/material	
Enclosure material (front)	
• Aluminum	Yes
Dimensions	
Width of the housing front	483 mm
Height of housing front	310 mm
Mounting cutout, width	450 mm
Mounting cutout, height	290 mm
Overall depth	55 mm
last modified:	08/16/2016