

SIMATIC IPC277E (Nanopanel PC); 9" Touch TFT; 2x 10/100/1000 Mbps Ethernet RJ45; 1x display port graphic; 1x USB 3.0; 2x USB 2.0; 1x serial (COM 1); CFast slot; 24 V DC power supply Celeron N2807 (2C/2T) 2 GB RAM; without operating system without mass storage, with CFast slot without SIMATIC software

General information

Product type designation	IPC277E
--------------------------	---------

Display

Design of display	9" TFT touch
-------------------	--------------

Screen diagonal	9 in
-----------------	------

Resolution (pixels)

- | | |
|-------------------------------|-----------|
| • Horizontal image resolution | 800 Pixel |
| • Vertical image resolution | 480 Pixel |

Backlighting

- | | |
|--------------------------------|----------|
| • MTBF backlighting (at 25 °C) | 80 000 h |
|--------------------------------|----------|

Control elements

Touch operation

- | | |
|--------------------------|------------------------|
| • Design as touch screen | Yes; analog, resistive |
|--------------------------|------------------------|

Installation type/mounting

central design	Yes
----------------	-----

Mounting in portrait format possible	Yes
--------------------------------------	-----

Power loss

In full configuration	29 W
-----------------------	------

Dimensions

Width of the housing front	274 mm
----------------------------	--------

Height of housing front	190 mm
-------------------------	--------

Mounting cutout, width	251 mm
------------------------	--------

Mounting cutout, height	166 mm
-------------------------	--------

Overall depth	77 mm
---------------	-------

Weights

Weight, approx.	1.95 kg
-----------------	---------

last modified: 11/28/2020