

SIMATIC IPC277G (nanopanel PC); 22" multi-touch (1920 x 1080); 3x 10/100/1000 Mbps Ethernet RJ45; 2x display port graphic; 4x USB 3.1, 2x M.2 extension slot; 24 V DC industrial power supply Atom X6414RE (4-core); 4 GB RAM; without COM; 256 GB Eco SSD; without hardware extension; Windows 10 IoT Enterprise 2019 LTSC, 64-bit, MUI (en/de/fr/it/es), ;

Display	
Design of display	22" TFT multi-touch
Screen diagonal	22 in
Resolution (pixels)	
• Horizontal image resolution	1 920 pixel
• Vertical image resolution	1 080 pixel
Backlighting	
• MTBF backlighting (at 25 °C)	30 000 h
Control elements	
Touch operation	
• Design as multi-touch screen	Yes; Projective-capacitive
Installation type/mounting	
central design	Yes
Mounting in portrait format possible	Yes
Power loss	
In full configuration	80 W
Dimensions	
Width of the housing front	529 mm
Height of housing front	331 mm
Mounting cutout, width	513 mm
Mounting cutout, height	315 mm
Overall depth	105 mm
Weights	
Weight, approx.	8.1 kg
last modified:	1/23/2023 