



Figure similar

Spare part SIPLUS HCS716I LA716 power output module with 16 channels max. 650 W each. For operation, a rack is required. The 5x 20 mm fuses 5AMP. quick-action are (replaceable) to be plugged onto open fuse holders; 2-phase line infeed via front-side 3-pole connection terminal. Radiator outlets via 2x8-pole pin connectors (not included in scope of supply)

General information	
Product brand name	SIPLUS
Type of control of heat emitters	Full-wave control
Installation type/mounting	
Mounting type	Mounting clip in the rack
Mounting position	vertical
Type of ventilation	Self ventilation or forced ventilation
Supply voltage	
Type of supply voltage	AC
Rated value (AC)	230 V
Relative negative tolerance	18 %
Relative positive tolerance	15 %
Connection method	
• Design of electrical connection for supply voltage	Terminal, 3-pin
— Connectable conductor cross-sections, solid	1x (0.5 ... 6 mm²)

— Connectable conductor cross-sections, finely stranded with wire end processing	1x (0.5 ... 4 mm ²)
— Connectable conductor cross-sections for AWG cables	22 ... 10
Power electronics	
Type of load	Ohmic load
Heating power	
• Power carrying capacity per output, max.	650 W
Connection method	
• Design of electrical connection at output for heating and fan	Socket strip, 8-pole
— Connectable conductor cross-sections, solid	1x (0.2 ... 1.5 mm ²)
Interfaces	
Interfaces/bus type	system interface
Interrupts/diagnostics/status information	
Diagnostics function	Voltage diagnostics
Diagnostic messages	
• Wire-break	Yes
• Fuse blown	Yes
• Heat emitter defect	Yes
Integrated Functions	
Monitoring functions	
• Temperature monitoring	Yes
Potential separation	
Design of electrical isolation	Optocoupler between main circuit and SELV / PELV
between the outputs	No
EMC	
EMC interference emission	in accordance with EN 61000-6-4:2007 + A1:2011
Electrostatic discharge acc. to IEC 61000-4-2	4 kV contact discharge / 8 kV air discharge
Field-related interference acc. to IEC 61000-4-3	10 V/m (80 ... 1 000 MHz), 3 V/m (1.4 ... 2.0 GHz), 1 V/m (2.0 ... 2.7 GHz)
Conducted interference due to burst acc. to IEC 61000-4-4	2 kV voltage supply cables / 2 kV signal cables
Conducted interference due to surge acc. to IEC 61000-4-5	on power supply and signal cables: 1 kV symmetrical, 2 kV unsymmetrical
Conducted interference due to high-frequency radiation acc. to IEC 61000-4-6	10 V (0.15 ... 80 MHz)
Degree and class of protection	
IP degree of protection	IP00
Standards, approvals, certificates	

Certificate of suitability	CE, KCC
KC approval	Yes
EAC (formerly Gost-R)	Yes
China RoHS compliance	Yes

Ambient conditions

Ambient temperature during operation

- min. 0 °C
- max. 55 °C

Ambient temperature during storage/transportation

- Storage, min. -40 °C
- Storage, max. 70 °C
- Transportation, min. -40 °C
- Transportation, max. 70 °C

Air pressure acc. to IEC 60068-2-13

- Operation, min. 860 hPa
- Operation, max. 1 080 hPa
- Storage, min. 660 hPa
- Storage, max. 1 080 hPa

Altitude during operation relating to sea level

- Installation altitude above sea level, max. 2 000 m

Shock testing

- Shock resistance acc. to IEC 60068-2-27 15 g / 11 ms / 3 shocks/axis
- Shock resistance acc. to IEC 60068-2-29 25 g / 6 ms / 1 000 shocks/axis

Dimensions

Width	31 mm
Height	233.4 mm
Depth	241 mm

last modified: 08/04/2018