



Figure similar

SIMATIC ET 200SP HA, ET 200SP, digital ex-i input module, DI 4xNAMUR, suitable for BaseUnit type X1, channel diagnostics

General information	
Product type designation	Ex-DI 4xNAMUR
Firmware version	V1.0
• FW update possible	Yes
usable BaseUnits	BU type X1
Product function	
• I&M data	Yes; I&M0 to I&M3
• Isochronous mode	No
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	STEP 7 V16 or higher with HSP
• STEP 7 configurable/integrated from version	STEP 7 V5.6 SP2 or higher
• PCS 7 configurable/integrated from version	V9.1
Operating mode	
• DI	Yes
• Counter	Yes
• MSI	Yes
Redundancy	
• Redundancy capability	No
Input current	
Current consumption (rated value)	50 mA
Current consumption, max.	55 mA
Encoder supply	
Number of outputs	4
Output voltage (DC)	8.2 V
Short-circuit protection	Yes
Power loss	
Power loss, typ.	1.2 W
Address area	
Address space per module	
• Inputs	10 byte; + 1 byte for QI information
• Outputs	10 byte
Hardware configuration	
Automatic encoding	
• Mechanical coding element	Yes
Selection of BaseUnit for connection variants	
• 2-wire connection	BU type X1
Digital inputs	

Number of digital inputs	4; NAMUR
Digital inputs, parameterizable	Yes
Pulse extension	Yes; 0.5 s, 1 s, 2 s
Time stamping	No
Edge evaluation	Yes; Positive edge, negative edge
Signal change flutter	Yes; 2 to 32 signal changes
Flutter observation window	Yes; 0.5 s, 1 s to 100 s in 1-s steps
Digital input functions, parameterizable	
- Counter — Number, max. — Counting frequency, max. — Counting direction up/down	2; Channel 0 and 1 5 kHz Yes; Up
Input voltage	
Rated value (DC)	8.2 V
Input current	
for 10 k switched contact	
— for signal "0"	Max. 1.2 mA
— for signal "1"	Min. 2.1 mA
for unswitched contact	
— for signal "0", max. (permissible quiescent current)	0.5 mA
— for signal "1"	typ. 8 mA
Input delay (for rated value of input voltage)	
for NAMUR inputs	
— at "0" to "1", max.	12 ms
— at "1" to "0", max.	12 ms
Cable length	
shielded, max.	500 m; Ex characteristic values must be observed; without shield applied on both sides and cable lengths of more than 200 m, measured value distortions can occur when using the inputs as counter/ frequency meter
unshielded, max.	300 m; Ex characteristic values must be observed; without shield applied on both sides and cable lengths of more than 200 m, measured value distortions can occur when using the inputs as counter/ frequency meter
Encoder	
Connectable encoders	
NAMUR encoder/changeover contact according to EN 60947	Yes
Single contact / changeover contact unconnected	Yes
Single contact / changeover contact connected with 10 kΩ	Yes
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
Diagnostic alarm	Yes
Maintenance interrupt	Yes
Hardware interrupt	Yes; channel by channel
Diagnoses	
Diagnostic information readable	Yes
- Monitoring the supply voltage — parameterizable	Yes Yes
Monitoring of encoder power supply	Yes
Wire-break	Yes; channel by channel
Short-circuit	Yes; channel by channel
Group error	Yes
Diagnostics indication LED	
MAINT LED	Yes; Yellow LED
Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
Channel status display	Yes; green LED
for channel diagnostics	Yes; red LED
for module diagnostics	Yes; green/red DIAG LED

Integrated Functions	
Measuring functions	
Accuracy	
— Frequency measurement	1 %
Ex(i) characteristics	
maximum values for connecting terminals for gas group IIC	
• U₀ (no-load voltage), max. • I₀ (short-circuit current), max. • P₀ (power output), max. • C₀ (permissible external capacity), max. • L₀ (permissible external inductivity), max. • U_m (voltage at non-intrinsically safe connecting terminals), max.	9.6 V 61 mA; applies for up to four circuits connected in parallel 145 mW; applies for up to four circuits connected in parallel 3.6 µF; applies for up to four circuits connected in parallel 13 mH; applies for up to four circuits connected in parallel 60 V
Potential separation	
Potential separation channels	
• between the channels • between the channels and backplane bus • between the channels and the power supply of the electronics	No Yes Yes; Electrical isolation between the channels and input voltage PME
Isolation	
Isolation tested with	further information on insulation can be found in the "ET 200SP HA / ET 200SP modules for devices in hazardous areas" System Manual
insulation of the field circuits to local ground acc. to IEC/EN 60079-11 tested with	707 V DC (type test)
Ambient conditions	
Ambient temperature during operation	
• horizontal installation, min. • horizontal installation, max. • vertical installation, min. • vertical installation, max.	-40 °C 70 °C -40 °C 60 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	2 000 m
Dimensions	
Width	20 mm
Height	73 mm
Depth	58 mm
Weights	
Weight, approx.	55 g
last modified:	5/20/2021 