

LOGO! 12/24RC, LOGIC MOD., DISPL. PU/I/O: 12/24V DC/RELAY, 8 DI (2AI)/4 DO; MEM 56 BLOCKS, EXPANDABLE WITH EXTRA MODULES

Installation type/mounting	
Mounting	on 35 mm DIN rail, 4 spacing units wide
Supply voltage	
Rated value (DC)	
• 12 V DC	Yes
• 24 V DC	Yes
Time of day	
Time switching clocks	
• Number	8
• Power reserve	80 h
Digital inputs	
Number of digital inputs	8; of which 2 analog are usable
Digital outputs	
Number of digital outputs	4; Relays
Short-circuit protection	No; external fusing necessary
Relay outputs	
Switching capacity of contacts	
— with inductive load, max.	3 A
— with resistive load, max.	10 A
EMC	
Emission of radio interference acc. to EN 55 011	
• Limit class B, for use in residential areas	Yes
Degree and class of protection	
Degree of protection acc. to EN 60529	
• IP20	Yes
Standards, approvals, certificates	
CE mark	Yes
CSA approval	Yes
UL approval	Yes
FM approval	Yes
developed in accordance with IEC 61131	Yes
according to VDE 0631	Yes

Marine approval	
• Marine approval	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	55 °C
Dimensions	
Width	72 mm; 4 WU
Height	90 mm
Depth	55 mm
last modified:	08.09.2015