

SITOP UPS1100 BATTERY MOD. 24 V/1.2 AH
SITOP UPS1100 BATTERY MODULE WITH SERVICE- FREE
SEALED LEAD BATTERIES FOR SITOP DC-UPS-MODULES 24 V
1.2 AH DC



Technical specifications	
Product	SITOP UPS1100
Product type	Battery module 1.2 Ah
Battery	1.2 A·h
Charging current charging voltage	
End-of-charge voltage at DC	
• at -10 °C recommended	28.02 V
• at 0 °C recommended	28.02 V
• at 10 °C recommended	27.8 V
• at 20 °C recommended	27.3 V
• at 30 °C recommended	26.8 V
• at 40 °C recommended	26.6 V
• at 50 °C recommended	26.3 V
Rated current value Iout rated	10 A
Permissible charging current, max.	0.3 A
Rated voltage Vout DC	24 V
Safety	

Short-circuit protection	Battery fuse 15 A/32 V (solid-state circuitry blade-type fuse + support)
Design of the overload protection	Valve control
Status display	LED green: Battery OK; LED flashing green: Error or warning; OFF: No communication

Safety

Protection class	Class III
CE mark	Yes
UL/cUL (CSA) approval	cURus-Recognized (UL 1778, CSA C22.2 No. 107.1), File E219627
Explosion protection	IECEx Ex nA nC IIC T4 Gc; cCSAus (CSA C22.2 No. 213-M1987, ANSI/ISA-12.12.01-2013) Class I, Div. 2, Group ABCD, T4
Approvals	Yes
Marine approval	GL, ABS
Degree of protection (EN 60529)	IP20

Operating data note

Operating data note	For storage, mounting and operation of lead-acid batteries, the relevant DIN/VDE regulations or country-specific regulations (e.g. VDE 0510 Part 2/EN 50272-2) must be observed. You must ensure that the battery site is sufficiently ventilated. Possible sources of ignition must be at least 50 cm away.
Ambient temperature - during operation - during transport - during storage	0 ... 40 °C -20 ... +50 °C -20 ... +50 °C
Relative temporary capacity loss at 20 °C in a month typical	3 %

Service life

Service life of lead-acid battery - typical Note - at 20 °C typical - at 30 °C typical - at 40 °C typical - at 50 °C typical	capacity falls to 50 % of original capacity 4 y 2 y 1 y 0.5 y
Ambient temperature during storage Note	Along with the storage and operating temperature, other factors such as the duration of the storage period and the charge status during storage have a decisive influence on the possible useful life. Batteries should therefore be stored as briefly as possible, always fully charged, and within the temperature range 0 to +20 °C.

Mechanics

Connection technology	screw-type terminals
Connection for power supply unit	1 screw terminal each for 0.2 ... 6 mm² for + BATT and - BATT

Type of electrical connection for control circuit and status message	1 screw terminal each for 0.14 ... 4 mm ²
Product component belonging to	Accessories pack with solid-state circuitry fuse 15 A
Width of the enclosure	89 mm
Height of the enclosure	130.3 mm
Depth of the enclosure	106.7 mm
Installation width	89 mm
Installation height	145.3 mm
Weight, approx.	1.9 kg
Number of cells	12
Installation	snaps onto DIN rail EN 60715 35x7.5/15 or keyhole mounting for hooking in to M4 screws
Number of cells	12
Equipment marking acc. to DIN EN 81346-2	G
Other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)