




SITOP BAT1600/BATT.MODUL/24V/38AH

SITOP BAT1600 24 V DC 38 Ah Pb battery module with maintenance-free closed lead-acid battery for SITOP UPS1600

Charging current charging voltage

end-of-charge voltage at DC

• at -10 °C recommended	28 V
• at 0 °C recommended	28 V
• at 10 °C recommended	27.8 V
• at 20 °C recommended	27.3 V
• at 30 °C recommended	26.8 V
• at 40 °C recommended	26.6 V
• at 50 °C recommended	26.3 V

Output

output current rated value	40 A
charging current maximum	9 A
output voltage at DC rated value	24 V

Safety

design of the overload protection	Valve control
display version for normal operation	Three-color: green = Buffer ready; yellow = Buffer endangered; red = Buffer not possible

Safety

operating resource protection class	Class III
protection class IP	IP20

Approvals

certificate of suitability	
• CE marking	Yes
• UL approval	Yes
• as approval for USA	UL-Listed (UL 621010, CSA C22.2 No. 107.1)
• CSA approval	Yes
• cCSAus, Class 1, Division 2	No
• ATEX	No
certificate of suitability	
• C-Tick	Yes
• shipbuilding approval	Yes
shipbuilding approval	ABS, DNV GL
Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	Yes
• DNV GL	Yes

environmental conditions

Operating data note	For storage, mounting and operation of batteries, the relevant DIN/VDE regulations or country-specific regulations (e.g. VDE 0510 Part 2/EN 50272-2) must be observed.
ambient temperature	
• during operation	-15 ... +50 °C

• during transport	-30 ... +70 °C
• during storage	-20 ... +40 °C
relative temporary capacity loss at 20 °C in a month typical	3 %
Service life	
service life of energy storage • typical • at 20 °C typical • at 30 °C typical • at 40 °C typical • at 50 °C typical	capacity falls to 80 % of original capacity (according to EUROBAT) 10 a 5 a 2.5 a 1.25 a
ambient temperature during storage	In addition to the storage temperature, additional factors, such as storage duration and charging status during storage, have a major impact on the potential service life. This means batteries should preferably be stored fully charged for short periods of time in a dry, cool and frost-proof (temperature range 0 to +20 °C) location.
Mechanics	
type of electrical connection • for power supply unit • for control circuit and status message	Plug-in terminals with screwed connection 1 screw terminal each for 0.5 ... 16 mm² for + BAT and - BAT 1 screw terminal each for 0.2 ... 2.5 mm²
product component included	2x Maxi Fuse 50 A/32 V
width of the enclosure	394 mm
height of the enclosure	212 mm
depth of the enclosure	165 mm
installation width	330 mm
mounting height	262 mm
required spacing • top • bottom • left • right	50 mm 50 mm 0 mm 0 mm
fastening method • wall mounting • standard rail mounting • S7 rail mounting	No No No
fastening method	Floor mounting
net weight	27.9 kg
number of cells	2
battery capacity	38 A·h
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

