

SIMATIC ET 200SP PS 24V/10A
SIMATIC ET 200SP PS 24V/10A Stabilized power supply Input:
120/230 V AC Output: 24 V DC/10 A



Input	
Input	1-phase AC
• Note	Automatic range selection
Supply voltage	
• 1 at AC Rated value	120 V
• 2 at AC Rated value	230 V
Input voltage	
• 1 at AC	85 ... 132 V
• 2 at AC	170 ... 264 V
Wide-range input	No
Overvoltage resistance	2.3 × Vin rated, 1.3 ms
Mains buffering at lout rated, min.	20 ms; at Vin = 93/187 V
Rated line frequency 1	50 Hz
Rated line frequency 2	60 Hz
Rated line range	47 ... 63 Hz
Input current	
• at rated input voltage 120 V	4.34 A
• at rated input voltage 230 V	1.92 A
Switch-on current limiting (+25 °C), max.	60 A

I^2t , max.	6.3 A ² ·s
Built-in incoming fuse	T 6.3 A/250 V (not accessible)
Protection in the mains power input (IEC 898)	recommended LS switch: B/C 10 A/6 A

Output

Output	Controlled, isolated DC voltage
Rated voltage Vout DC	24 V
Total tolerance, static ±	3 %
Static mains compensation, approx.	0.1 %
Static load balancing, approx.	1 %
Residual ripple peak-peak, max.	150 mV
Residual ripple peak-peak, typ.	50 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	240 mV
Spikes peak-peak, typ. (bandwidth: 20 MHz)	150 mV
Adjustment range	22.8 ... 28 V
Product function Output voltage adjustable	Yes
Output voltage setting	via potentiometer
Status display	Green LED for 24 V OK
Signaling	Relay contact (NO contact, rating 60 V DC/ 0.3 A) for "24 V OK"
On/off behavior	Overshoot of Vout < 3 %
Startup delay, max.	0.3 s
Voltage rise, typ.	30 ms
Rated current value Iout rated	10 A
Current range	0 ... 12 A
• Note	10 A up to +60°C; +60 ... +70 °C: Derating 3%/K
Supplied active power typical	240 W
Short-term overload current	
• on short-circuiting during the start-up typical	30 A
• at short-circuit during operation typical	30 A
Duration of overloading capability for excess current	
• on short-circuiting during the start-up	750 ms
• at short-circuit during operation	800 ms
Parallel switching for enhanced performance	Yes
Numbers of parallel switchable units for enhanced performance	2

Efficiency

Efficiency at Vout rated, Iout rated, approx.	90 %
Power loss at Vout rated, Iout rated, approx.	26 W
Power loss [W] during no-load operation maximum	2.8 W

Closed-loop control

Dynamic mains compensation (Vin rated ±15 %), max.	0.3 %
--	-------

Dynamic load smoothing (I _{out} : 10/90/10 %), U _{out} ± typ.	3 %
Load step setting time 10 to 90%, typ.	1 ms
Load step setting time 90 to 10%, typ.	1 ms

Protection and monitoring

Output overvoltage protection	protection against overvoltage in case of internal fault V _{out} < 31.8 V
Current limitation	14 ... 15 A
Property of the output Short-circuit proof	Yes
Short-circuit protection	Constant current characteristic
Enduring short circuit current RMS value • typical	14.1 A
Overcurrent overload capability in normal operation	overload capability 150 % I _{out} rated up to 5 s/min
Overload/short-circuit indicator	-

Safety

Primary/secondary isolation	Yes
Galvanic isolation	Safety extra-low output voltage U _{out} acc. to EN 60950-1 and EN 50178
Protection class	Class I
Leakage current • maximum • typical	3.5 mA 1 mA
CE mark	Yes
UL/cUL (CSA) approval	cULus-Listed (UL61010-2-201, CSA C22.2 No.142), cCSAus (CSA C22.2 No. 60950-1, UL 60950-1)
CB approval	Yes
Marine approval	BV, DNV GL
Degree of protection (EN 60529)	IP20

EMC

Emitted interference	EN 61000-6-3 Class B
Supply harmonics limitation	EN 61000-3-2
Noise immunity	EN 61000-6-2

Operating data

Ambient temperature • during operation — Note • during transport • during storage	-30 ... +70 °C with natural convection -40 ... +85 °C -40 ... +85 °C
Humidity class according to EN 60721	Climate class 3K3, no condensation

Mechanics

Connection technology	Push-in terminals
-----------------------	-------------------

Connections	
• Supply input	L, N, PE: 1 push-in terminal each for 0.2 ... 2.5 mm ² single-core/finely stranded
• Output	+, -: 2 push-in terminals each for 0.2 ... 2.5 mm ²
• Auxiliary	Signaling contact: 2 push-in terminals for 0.2 ... 2.5 mm ²
Connections signaling contact	2 push-in terminals for 0.2 ... 2.5 mm ²
Product function	
• removable terminal at input	Yes
• removable terminal at output	Yes
Width of the enclosure	160 mm
Height of the enclosure	117 mm
Depth of the enclosure	74 mm
Required spacing	
• top	50 mm
• bottom	50 mm
• left	0 mm
• right	0 mm
Weight, approx.	0.7 kg
Product feature of the enclosure housing for side-by-side mounting	Yes
Installation	Snaps onto DIN rail EN 60715 35x7.5/15
Electrical accessories	Redundancy module, buffer module, selectivity module, DC UPS
MTBF at 40 °C	1 114 510 h
Other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)