

SIEMENS

Product data sheet

6ES7142-4BF00-0AA0


SIMATIC DP,
ELECTRONIC MODULES FOR ET200PRO 8 DO DC
24V,
0.5A MODULE DIAGNOSTICS;
INCLUSIVE BUS MODULE,
CONNECTING MODULE IO 6ES7194-4..00-0AA0
MUST BE ORDERED SEPERATELY

FH technology

Module for failsafe applications

No

Supply voltage

Load voltage 2L+

Rated value (DC)

24 V

Short-circuit protection

Yes ; per channel, electronic

Reverse polarity protection

Yes ; against destruction; load increasing

Input current

from load voltage 2L+ (without load), max.

30 mA

from backplane bus 3.3 V DC, max.

30 mA

Power losses

Power loss, typ.

2 W

Address area

Address space per module

with packing

8 bit

without packing	1 byte
Digital outputs	
Number/binary outputs	8
Functionality/short-circuit strength	Yes ; per channel, electronic
Response threshold, typ.	0,7
Limitation of inductive shutdown voltage to	2L+ (-47 V)
Lamp load, max.	5 W
Controlling a digital input	Yes ; Isolation between 1L+ and 2L+ is no longer provided, as 1M and 2M are jumpered
Load resistance range	
lower limit	48 Ω
upper limit	4 k Ω
Output voltage	
for signal "1", min.	2L+ (-0.8 V)
Output current	
for signal "1" rated value	0.5 A
for signal "0" residual current, max.	0.5 mA
Parallel switching of 2 outputs	
for increased power	No
for redundant control of a load	Yes
Switching frequency	
with resistive load, max.	100 Hz
with inductive load, max.	0.5 Hz
on lamp load, max.	1 Hz
Aggregate current of outputs (per group)	
all mounting positions	
up to 55 °C, max.	4 A
Cable length	
Cable length, shielded, max.	30 m
Cable length unshielded, max.	30 m
Interrupts/diagnostics/status information	
Diagnostic messages	
Diagnostic functions	Yes
Diagnostic information readable	Yes

Short circuit	Yes ; Short-circuit of outputs to ground; module by module
Diagnostics indication LED	
Group error SF (red)	Yes
Status indicator digital output (green)	Yes
Galvanic isolation	
Galvanic isolation digital outputs	
between the channels	No
between the channels and the backplane bus	Yes
Isolation	
Isolation checked with	500 V DC
Dimensions	
Width	45 mm
Height	130 mm
Depth	35 mm
Weight	
Weight, approx.	140 g
Status	Jul 17, 2012