



SIMATIC ET 200MP, multi-fieldbus, interface module IM 155-5 MF HF, IM 155-5 MF HF, EtherNet/IP and Modbus TCP, 2 flexible ports via plug-in SIMATIC BusAdapter (sold separately), max. 30 I/O modules, multi-hot-swap with active backplane (sold separately), IRT with 250 µs, shared device with 4 controllers (1440 bytes each), 256 bytes per I/O module, MRP, MRPD, S2 redundancy, PN security class 1, optional cable grip (sold separately) PN security class 1, optional cable grip (sold separately)

General information	
Product type designation	IM 155-5 MF HF
HW functional status	From FS01
Firmware version	V5.0
• FW update possible	Yes
Vendor identification (VendorID)	002AH
Device identifier (DeviceID)	0312H
Product function	
• I&M data	Yes; I&M0 to I&M3
• Module swapping during operation (hot swapping)	Yes; In combination with active backplane bus
• Isochronous mode	No
• Tool changer	No
• Local coupling, IO data	No
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	V19
• STEP 7 configurable/integrated from version	use GSD file
• PROFINET from GSD version/GSD revision	GSDML V2.43
Configuration control	
via dataset	Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Short-circuit protection	Yes
Mains buffering	
• Mains/voltage failure stored energy time	10 ms
Input current	
Current consumption (rated value)	0.16 A; at 24 V DC and without load
Current consumption, max.	1.2 A
Inrush current, max.	13 A
I ² t	0.1 A ² ·s
Power	
Infeed power to the backplane bus	16 W
Power available from the backplane bus	3.4 W; in case of operation with separate system power supply to the left of IM
Power loss	
Power loss, typ.	4.3 W
Address area	
Address space per module	
• Address space per module, max.	256 byte; For input and output data respectively

Address space per station	
• Address space per station, max.	1 440 byte; For input and output data respectively
Hardware configuration	
Integrated power supply	Yes; 16 W
System power supply can be plugged in to left of IM	Yes; only with design with U-connectors
Number of permissible power segments	3; incl. interface module
Rack	
• Modules per rack, max.	30; I/O modules
Submodules	
• Number of submodules per station, max.	256; 9 per I/O module
Interfaces	
Number of PROFINET interfaces	1; 2 ports (switch)
1. Interface	
Interface types	
• RJ 45 (Ethernet)	Yes; with BusAdapter
• Number of ports	2; with BusAdapter
• integrated switch	Yes
• BusAdapter (PROFINET)	Yes; BA 2x RJ45, BA 2x FC, BA 2x M12
Protocols	
• PROFINET IO Device	Yes
• Open IE communication	Yes
• Media redundancy	Yes; PROFINET MRP client / HRP client
PROFINET IO Device	
Services	
— IRT	Yes; 250 µs to 4 ms in 125 µs frame
— PROFIenergy	No
— Prioritized startup	No
— Shared device	Yes
— Number of IO Controllers with shared device, max.	4
Interface types	
RJ 45 (Ethernet)	
• Transmission procedure	PROFINET with 100 Mbit/s full duplex (100BASE-TX)
• 100 Mbps	Yes
• Autonegotiation	Yes
• Autocrossing	Yes
Protocols	
Modbus TCP	No
Redundancy mode	
• PROFINET system redundancy (S2)	Yes; NAP S2
— on S7-1500R/H	Yes
— on S7-400H	Yes; use GSD file
• PROFINET system redundancy (R1)	No
• H-Sync forwarding	Yes
Media redundancy	
— MRP	Yes
— MRPD	Yes
Open IE communication	
• TCP/IP	Yes
• UDP	Yes
• SNMP	Yes
• LLDP	Yes
• ARP	Yes
• IGMP	Yes
• Multicast	Yes
• Broadcast	Yes
• IPv4	Yes
Isochronous mode	
Equidistance	No
Interrupts/diagnostics/status information	
Status indicator	Yes

Alarms	Yes
Diagnostics function	Yes
Diagnostics indication LED	
• RUN LED	Yes; green LED
• ERROR LED	Yes; red LED
• MAINT LED	Yes; Yellow LED
• Connection display LINK TX/RX	Yes; 2x green LEDs on BusAdapter
Potential separation	
between backplane bus and electronics	No
between PROFINET and all other circuits	Yes; 1500 V AC (type test)
between supply and all other circuits	No
Permissible potential difference	
between different circuits	Safety extra low voltage SELV
Isolation	
Isolation tested with	707 V DC (type test)
Standards, approvals, certificates	
Network loading class	3
product functions / security / header	
PROFINET Security Class	1
signed firmware update	Yes
Secure Boot	Yes
safely removing data	Yes
data integrity	Yes
Ambient conditions	
Ambient temperature during operation	
• horizontal installation, min.	-30 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	-30 °C
• vertical installation, max.	40 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
connection method	
ET-Connection	
• via BU/BA Send	No
Mechanics/material	
Strain relief	Yes; Optional
Dimensions	
Width	35 mm
Height	147 mm
Depth	129 mm
Weights	
Weight, approx.	260 g; without BusAdapter

last modified:

7/26/2024 