

ACTIVE FIELD SPLITTER AFS FOR PROFIBUS PA FOR
FOUNDATION FIELDBUS H1,
FOR ENHANCED TEMPERATURE RANGE PROTECTION
CLASS IP 66

General information	
Hardware product version	01
Product function	
Repeater function	No
Operator control and monitoring	
Illuminant	LED
Supply voltage	
permissible range, lower limit (DC)	16 V
permissible range, upper limit (DC)	32 V
Reverse polarity protection	Yes ; only in conjunction with FDC 157
Overvoltage protection	No
Input current	
Current consumption (in no-load operation), typ.	24 mA
Power loss	
Power loss, typ.	864 mW
Power loss, max.	2.13 W
Interfaces	
PROFIBUS DP	No
FOUNDATION Fieldbus H1	Yes
AS-Interface	No
PROFIBUS PA	
PROFIBUS PA	Yes
Transmission rate, max.	31.25 kbit/s
Interrupts/diagnostics/status information	
Status indicator	Yes
Alarms	
Alarms	No
Diagnostic messages	
Diagnostic functions	Yes
Diagnostics indication LED	

Status main line	Yes
Main line failure	Yes
Status/fault spur line	Yes
automatic bus termination	No
Galvanic isolation	
between main line and spur lines	No
Degree and class of protection	
IP66	Yes
Standards, approvals, certificates	
Use in hazardous areas	
EX Zone 1	No
EX zone 11	No
EX zone 2	Yes
EX zone 22	Yes
Class I Zone 1	No
Class I Zone 2, Division 2	Yes
Ambient conditions	
Operating temperature	
min.	-40 °C
max.	70 °C
Storage/transport temperature	
min.	-40 °C
max.	85 °C
Relative humidity	
Operation, max.	95 %
Connection method	
Main line	
Number of main lines	2
Design of terminals	Screw terminal block
Type of connection (enclosure cable gland)	M16
Type of cable	Type A
Cable diameter, min.	4 mm
Cable diameter, max.	9 mm
Conductor cross-section, min.	0.2 mm ²
Conductor cross-section, max.	2.5 mm ²
permissible main line current	1 A
Spur line	
Number of spur lines	2

Type of connection (enclosure cable gland)	M16
Type of cable	Type A
Cable diameter, min.	4 mm
Cable diameter, max.	9 mm
Conductor cross-section, min.	0.2 mm ²
Conductor cross-section, max.	2.5 mm ²
intrinsically safe according to FISCO model	No
Dimensions	
Width	220 mm
Height	120 mm ; without screw glands
Depth	83 mm
Weights	
Weight, approx.	2000 g
Status	Jul 21, 2014