



SIMATIC ET 200SP, BaseUnit BU20-P16+A0+2B, BU-TYPE U0,
Packaging Unit: 10 Pieces, Push-in terminals, w/o AUX-terminals, bridged
to left BU, WxH: 20mm x 117mm

General information	
Product type designation	BU type U0
HW functional status	FS10 and higher
Supply voltage	
Rated value (DC)	See manual
• For P1 and P2 bus	120 V
• For AUX bus	120 V; Equal potential group to P1/P2 bus or PE
• for process terminals	120 V
Rated value (AC)	See manual
• For P1 and P2 bus	277 V
• For AUX bus	277 V; Equal potential group to P1/P2 bus or PE
• for process terminals	277 V
Mains filter	
• integrated	No
Current carrying capacity	
up to 60 °C, max.	10 A
For P1 and P2 bus, max.	10 A
For AUX bus, max.	10 A
For process terminals, max.	10 A; Point of contact, derating depends on the module
Hardware configuration	
Automatic encoding	Yes
Formation of potential groups	
• New potential group	No
• Potential group continued from the left	Yes
Slots	
• Number of slots	1
Potential separation	
between backplane bus and supply voltage	Yes
between process terminals and supply voltage	Yes; Not applicable for process terminals 15 and 16
between power bus and supply voltage	No
Isolation	
Isolation tested with	3 100 V DC
Ambient conditions	
Ambient temperature during operation	
• horizontal installation, min.	-30 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	-30 °C
• vertical installation, max.	50 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	3 000 m

connection method / header	
Terminals	
- Terminal type - system-integrated shield connection - Conductor cross-section, min. - Conductor cross-section, max. - Number of process terminals to I/O module - Number of terminals to AUX bus - Number of add-on terminals - Number of terminals with connection to P1 and P2 bus	Push-in terminal Yes; Optional 0.14 mm ² ; 0.2 mm ² without wire end ferrule 2.5 mm ² ; 1.5 mm ² with wire end ferrule 16 0 0 2
Dimensions	
Width	20 mm
Height	117 mm
Depth	35 mm
Weights	
Weight, approx.	50 g
last modified:	1/20/2023 