



LITHIUM BATTERY 3.6 V FOR TD17, OP17,
OP25, OP27, OP35, OP37, TP27, TP37,
OP/TP270, MP 270, MP 270B, MP 370,
C7-621, C7-623, C7-624,
C7-626 AND PG 7XX,
CABLE APPROX. 250 MM BATTERY AND ADAPTER
CABLE

Installation type/mounting	
Wall mounting/direct mounting possible	Yes ; in HMI devices, battery compartment
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	3.6 V ; 1.6 Ah
Battery	
Design	
Special design	Yes ; 2/3 AA
Technology	
Lithium-ion	Yes ; SL-361
Standards, approvals, certificates	
CE mark	Yes
Ambient conditions	
Operating temperature	
Operating temperature range, min.	0 °C
Operating temperature range, max.	55 °C
Storage/transport temperature	
min.	-55 °C

max.	85 °C
Relative humidity	
Operation, max.	90 %
Dimensions	
Height	33 mm ; Length
Thickness	14.7 mm ; Diameter
Weights	
Weight without packaging	14 g
Scope of supply	
Delivery unit in items	1 ; Incl. 45 mm + 210 mm connecting cable
Other	
Note:	for TD17, OP17, OP25, OP27, OP35, OP37, TP27, TP37, OP/TP270, MP 270, MP 270B, MP 370, C7-621, C7-623, C7-624, C7-626 and PG 7xx
Usable in the following products	
Product 1	6AV3017-1NE30*
Product 2	6AV3617-4EB42-0AA0
Product 3	6AV3617-1JC00*
Product 4	6AV3617-1JC20*
Product 5	6AV3617-1JC30*
Product 6	6AV3525-1EA41*
Product 7	6AV3525-1EA01-0AX0
Product 8	6AV3627-1JK00-0AX0
Product 9	6AV3627-1LK00-1AX0
Product 10	6AV3627-7JK00-0AX0
Product 11	6AV3535-1TA41-0BX1
Product 12	6AV3535-1FA01*
Product 13	6AV3535-1FA41-0BX1
Product 14	6AV3637-1ML00*
Product 15	6AV3637-1LL00*
Product 16	6AV3627-1NK00*
Product 17	6AV3627-1QK00*
Product 18	6AV3627-1QL00-0AX0
Product 19	6AV3637-1PL00-0AX0
Product 20	6AV6542-0C*
Status	Jul 21, 2014