## **SIEMENS**

## **Data sheet**

## 6ES7647-8AA50-1AA4

SIMATIC IPC227D (Nanobox PC) 1x DVI-I graphics card connection; 2x 10/100/1000 Mbps Ethernet RJ45; 4xUSB V2.0 (high current); Compact Flash slot; 24 V DC industrial power supply ATOM E620 (600 MHz), 512 MB RAM 2 GB SIMATIC PC CompactFlash COM1: RS232; WES 2009 SP3 (CF 2 GB or more/SSD/HD) without SIMATIC software Device type: Basic Side mounting

	SiMATIC software Device type. Dasic Side mounting
General information	
Product type designation	IPC227D
Installation type/mounting	
Design	Box PC, built-in unit
Supply voltage	
Type of supply voltage	24 V DC
Mains buffering	
Mains/voltage failure stored energy time	20 ms
Processor	
Processor type	Intel Atom E6x0
Drives	
Hard disk	CF or SSD or HD
SSD	Yes; ≥ 240 GB optional
Memory	
Main memory	512 MB to 2 GB
Capacity of main memory, max.	2 Gbyte
Data areas and their retentivity	
Retentive data area (incl. timers, counters, flags),	512 kbyte
max.	
Hardware configuration	
Slots	
• free slots	1x PCle x1 (optional)
<ul> <li>Number of compact flash slots</li> </ul>	1; CompactFlash
Interfaces	
USB port	4x USB 2.0 high speed/high current
Connection for keyboard/mouse	USB / USB
serial interface	COM1: 1x RS 232 or RS 485 or CAN
Video interfaces	
Graphics interface	DVI-D
Industrial Ethernet	

<ul><li>Industrial Ethernet interface</li><li>— 100 Mbps</li><li>— 1000 Mbps</li></ul>	2x Fast Ethernet Yes Yes	
Integrated Functions  Monitoring functions		
Temperature monitoring	Yes	
Watchdog	Yes	
Status LEDs	Yes	
● Fan	No	

Degree and class of protection	
IP (at the front)	IP20

Standards, approvals, certificates		
Approval	CE (industry), UL, cULus	
CE mark	Yes	
cULus	Yes	
KC approval	Yes	
Dust protection	Protection against foreign bodies > 1 mm	
Marine approval		
<ul> <li>Germanischer Lloyd (GL)</li> </ul>	Yes	
<ul> <li>American Bureau of Shipping (ABS)</li> </ul>	Yes	
Bureau Veritas (BV)	Yes	
<ul><li>Det Norske Veritas (DNV)</li></ul>	Yes	
<ul> <li>Lloyds Register of Shipping (LRS)</li> </ul>	Yes	

Ambient conditions	
Ambient temperature during operation	
Ambient temperature during operation	0 °C to 50 °C

Operating systems		
Operating system	Windows 7 Ultimate (Multi-Language) 32-bit / 64-bit	
pre-installed operating system	Yes	
without operating system	Yes	
ore-installed operating system		
Windows XP Professional	Yes	
• Windows 7	Yes	

**last modified:** 03/02/2019