

SIMATIC PCS 7 SYSTEM EXPANSION CARD W/OPROCESS OBJECTS FOR PCS 7 CPU410-5H

General information	
Product type designation	PCS 7 System Expansion Card PO 0
HW functional status	3
Firmware version	V2.0
Design of PLC basic unit	With Conformal Coating (ISA-S71.04 severity level G1; G2; G3) and operating temperature to 70 °C
Memory	
PCS 7 process objects	0; PO for CPU 410-5H; expandable by means of CPU 410 Expansion Pack PO 100 or PO 500
Work memory	
• integrated	0 Mbyte
• expandable	Yes, by means of CPU 410 Expansion Pack PO 100 or PO 500
CPU-blocks	
DB	
• Size, max.	64 kbyte; The total size of all data blocks generated with the SFC 22 (CREATE_DB) is limited to 256 KB
Address area	
I/O address area	
• Inputs	Use of 16 KB in the CPU 410-5H
• Outputs	Use of 16 KB in the CPU 410-5H
of which distributed	
— DP interface, inputs	6 kbyte; up to 2 800 IOs (channels)
— DP interface, outputs	6 kbyte; up to 2 800 IOs (channels)
— PROFINET interface, inputs	8 kbyte; up to 3 800 IOs (channels)
— PROFINET interface, outputs	8 kbyte; up to 3 800 IOs (channels)
Process image	
• Inputs, default	Total peripheral address range, cannot be changed
• Outputs, default	Total peripheral address range, cannot be changed
Digital channels	
• Inputs	131 072; max.
— of which central	131 072; max.
• Outputs	131 072; max.
— of which central	131 072; max.
Analog channels	
• Inputs	8 192; max.

- of which central 8 192; max.
- Outputs 8 192; max.
- of which central 8 192; max.

Standards, approvals, certificates

CE mark	Yes
CSA approval	Yes
UL approval	Yes
cULus	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
Use in hazardous areas	
• ATEX	ATEX II 3G Ex nA IIC T4 Gc

Ambient conditions

Ambient temperature during operation	
• min.	0 °C
• max.	70 °C

Configuration

Configuration software	
• STEP 7	No
Programming	
Programming language	
— LAD	No
— FBD	No
— STL	No
— SCL	Yes
— CFC	Yes
— GRAPH	No
— HiGraph®	No

Dimensions

Width	8 mm
Height	16 mm
Depth	25 mm

Weights

Weight, approx.	20 g
last modified:	01/04/2018