

SIMATIC PCS 7, system expansion card, up to 16 MB work memory and R1 license, with 8 KB each inputs and outputs, for PCS 7 CPU 410-5H

General information	
Product type designation	CPU 410 System Expansion Card 16 MB incl. R1
HW functional status	3
Firmware version	V2.0
Design of PLC basic unit	With Conformal Coating (ISA-S71.04 severity level G1; G2; G3) and operating temperature to 70 °C
Memory	
Work memory	
- integrated - integrated (for program) - integrated (for data) - expandable	use of max. 16 MB work memory in the CPU 410-5H use of max. 8 MB work memory in the CPU 410-5H use of max. 8 MB work memory in the CPU 410-5H No
Address area	
I/O address area	
- Inputs - Outputs	use of 8 KB in the CPU 410-5H use of 8 KB in the CPU 410-5H
Process image	
- Inputs, default - Outputs, default	Total peripheral address range, cannot be changed Total peripheral address range, cannot be changed
Digital channels	
- Inputs — of which central - Outputs — of which central	65 536; max. 65 536; max. 65 536; max. 65 536; max.
Analog channels	
- Inputs — of which central - Outputs — of which central	4 096; max. 4 096; max. 4 096; max. 4 096; max.
Standards, approvals, certificates	
CE mark	Yes
CSA approval	Yes
UL approval	Yes
cULus	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
Use in hazardous areas	
ATEX	ATEX II 3G Ex ec IIC T4 Gc
Ambient conditions	
Ambient temperature during operation	
- min. - max.	0 °C 70 °C
configuration / header	
Configuration software	
STEP 7	Yes
configuration / programming / header	
Programming language	
— LAD	Yes

- FBD
- STL
- SCL
- CFC
- GRAPH
- HiGraph®

Yes
Yes
Yes
Yes
Yes
Yes

Dimensions

Width	8 mm
Height	16 mm
Depth	25 mm

Weights

Weight, approx.	20 g
-----------------	------

last modified:

7/28/2021 