

SIMATIC PCS 7 Industrial Workstation IPC647D; (Rack PC, 19", 2HE), Interfaces: 2x Gbit LAN (RJ45), 1x DVI-I, 2x Display Port; 1x COM, 2x PS/2, Audio; 2x USB 3.0; 2x USB 2.0 on rear, 1x USB 3.0; 1x USB 2.0, on front; 1x USB 3.0 internal; Temperature and fan monitoring Watchdog; card retainer; Core I5-4570TE (2C/4T, 2.7 GHz, 4 MB cache, TB, VT-D, AMT); OS Client; 1x 500 GB HDD SATA; internal, 0.5 G vibration, 5 G shock, 8 GB DDR3 SDRAM (2 x 4 GB), Dual Channel; Without additional system bus communication cards; PCS 7 V9.0 SP2 pre-installed Windows 10 IoT Enterprise 2015 LTSB, 64 bit, MUI (en, de, fr, it, es, cn) bus module 4 slots: 2x PCI, 2x PCIE X16 (8 lane), DVD +/-RW (slim); + multi monitor 2 screens VIA Onboard interfaces + 1x adapter cable (Display Port according to DVI-D); 100/240V industrial power supply unit with NAMUR; power supply cable Europe

## Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)

<https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com>

