

SIMATIC PCS 7 Industrial Workstation IPC647D; (Rack PC, 19", 2HE), Interfaces: 2x Gbit LAN (RJ45), 1x DVI-I, 2x Display Port; 1x COM, 2x PS/2, Audio; 2x USB 3.0; 2x USB 2.0 on rear, 1x USB 3.0; 1x USB 2.0, on front; 1x USB 3.0 internal; Temperature and fan monitoring Watchdog; card retainer; Xeon E3-1268LV3 (4C/8T, 2.3 GHz, 8 MB cache, TB, VT-D, AMT); OS Client; 1x 1 TB HDD SATA in removable frame, on front; 8 GB DDR3 SDRAM (2 x 4 GB), Dual Channel; Without additional system bus communication cards; PCS 7 V9.0 SP2 pre-installed Windows 10 IoT Enterprise 2015 LTSP, 64 bit, MUI (en, de, fr, it, es, cn) bus module 4 slots: 2x PCI, 2x PCIE X16 (8 lane), DVD +/-RW (slim); + multi monitor 4 screens (combined, onboard interfaces (2 x DP) + Dual Head PCIE X16 board (2 x DP)), incl. 1XDP to DVI-D adapter cable, incl. 1xDual DVI-I adapter for Dual Head PCIE X16 board 2 x 100/240V redund. power supply unit; without power supply cable

last modified:

11/24/2021 