

SIMATIC Field PG M6 Comfort; i5-8400H (2.5 to 4.2 GHz; 4 kernels + hyper-threading; 8 MB Smart Cache); 15.6" display; Full HD (1920 x 1080); WLAN 802.11ac & Bluetooth V5.0; DVD +/-RW; UHD Graphics 630; 1x 8 GB DDR4 SD-RAM SO-DIMM; 256 GB SSD SATA (2.5"); without S5 interface, without S5-EPROMMER Power cable with power plug; Europe; Keyboard: QWERTZ/QWERTY (Germany); without NVME (M.2); Windows 10 Enterprise (Version 1903), 64-bit; License for STEP 7 Professional V16; WinCC Advanced V16; Safety Advanced V16; SINEMA RC Client 2.0; Version of the software V16.0.0.0

General information	
Design of the programming device	Notebook
Display	
Design of display	15.6" full HD display in 16:9 format
Resolution (pixels)	
• Horizontal image resolution	1 920 Pixel
• Vertical image resolution	1 080 Pixel
General features	
• Non-reflecting	Yes
• Luminance	300 cd/m ²
Backlighting	
• Type of backlighting	LED
Control elements	
Keyboard fonts	
• Design	QWERTZ/QWERTY or AZERTY (French); 87 keys
Touch operation	
• Integrated touch pad	Yes; Clickpad
Supply voltage	
Design of the power supply	External wide-range power supply; 3-pole
permissible range, lower limit (AC)	100 V; ±10 %, sinusoidal
permissible range, upper limit (AC)	240 V; ±10 %, sinusoidal
Line frequency	
• permissible range, lower limit	47 Hz
• permissible range, upper limit	63 Hz
Processor	
Processor type	Intel Core i5-8400H (2.5 to 4.2 GHz, 4 cores and hyper-threading, 8 MB Smart Cache) or i7-8850H (2.6 to 4.3 GHz 6 cores and hyper-threading, 9 MB Smart Cache)

Chipset	Intel CM246
Hyper-threading	Yes
Turbo Boost Technology 2.0	Yes
Graphic	
Graphics controller	Intel® UHD Graphics 630
Drives	
SSD	Yes; Easy to replace
• Memory capacity	256 Gbyte
TPM Security Chip	Yes; 2.0 (version for China without TPM)
Memory	
Work memory	
• Number of slots	2
Accumulator	
Replaceable	Yes; Lithium-ion battery
Capacity	8.25 A·h
Interfaces	
Number of interfaces PROFIBUS DP	1
Number of RS 232 interfaces	1; 25-pin socket
Number of USB interfaces	4
• Type A	3; 1x USB port incl. integrated charging function for USB devices (e.g. smartphone) - also with device switched off
• Type C	1; USB 3.1 Gen. 2
Number of chip-card readers	1; Smart Card Reader (ISO/IEC 7816)
Bluetooth radio standard	Yes; V5.0
Multimedia card/SD card slot	2 in 1 (SDHC UHS-II, MMC)
Card reader for SIMATIC memory cards	SIMATIC memory cards (for S7-300/400), SMC (for S7-1x00), SIMATIC micro memory card (for S7-300/C7/ET 200) - including programming interfaces
Universal Audio Jack	Yes; Audio socket for 3.5 mm jack
Video interfaces	
• analog video signal (VGA)	Yes; via adapter from DVI to VGA
• DVI-I	Yes; 1x
• DisplayPort	Yes; 1x
Industrial Ethernet	
• Industrial Ethernet interface	2x Ethernet (RJ45)
— 100 Mbps	Yes
— 1000 Mbps	Yes
• Wake on LAN	Yes
• IAMT (Intel Active Management Technology)	Yes
WLAN	
• Type	802.11ac

EMC

Interference immunity against discharge of static electricity

- | | |
|---|---|
| <ul style="list-style-type: none"> • Interference immunity against discharge of static electricity acc. to IEC 61000-4-2 | Yes; ± 4 kV contact discharge acc. to IEC 61000-4-2, ESD; ± 8 kV air discharge acc. to IEC 61000-4-2, ESD |
|---|---|

Interference immunity to cable-borne interference

- | | |
|--|---|
| <ul style="list-style-type: none"> • Interference immunity on supply cables | ± 2 kV (according to IEC 61000-4-4, burst); ± 1 kV (according to IEC 61000-4-5, surge pulse/line to line); ± 2 kV (according to IEC 61000-4-5, surge pulse/line to ground) |
| <ul style="list-style-type: none"> • Interference immunity on signal cables | ± 1 kV (according to IEC 61000-4-4, burst, length < 30 m); ± 2 kV (according to IEC 61000-4-4, burst, length > 30 m); ± 2 kV (according to IEC 61000-4-5, surge sym./line to ground, length > 30 m) |

Standards, approvals, certificates

CE mark	Yes
CSA approval	Yes
UL approval	Yes
DIN/ISO 9001	Yes

Ambient conditions

Ambient temperature during operation

- | | |
|--|---------------------------------------|
| <ul style="list-style-type: none"> • min. | 5 °C; Max. 10 °C/h (no condensation) |
| <ul style="list-style-type: none"> • max. | 40 °C; Max. 10 °C/h (no condensation) |

Ambient temperature during storage/transportation

- | | |
|--|--|
| <ul style="list-style-type: none"> • min. | -20 °C; Max. 20 °C/h (no condensation) |
| <ul style="list-style-type: none"> • max. | 60 °C; Max. 20 °C/h (no condensation) |

Relative humidity

- | | |
|---|--|
| <ul style="list-style-type: none"> • Operation, min. | 5 %; At 30 °C/h (no condensation); Tested according to IEC 60068-2-78, IEC 60068-2-30, IEC 60068-2-14 |
| <ul style="list-style-type: none"> • Operation, max. | 85 %; At 30 °C/h (no condensation); Tested according to IEC 60068-2-78, IEC 60068-2-30, IEC 60068-2-14 |

Vibrations

- | | |
|--|-----|
| <ul style="list-style-type: none"> • Operation, tested according to IEC 60068-2-6 | Yes |
|--|-----|

Shock testing

- | | |
|--|-----|
| <ul style="list-style-type: none"> • tested according to IEC 60068-2-27 | Yes |
|--|-----|

Operating systems

pre-installed operating system

- | | |
|--|-----------------------------------|
| <ul style="list-style-type: none"> • Windows 10 | Yes; Windows 10 Enterprise 64-bit |
|--|-----------------------------------|

Software

Preinstalled

- | | |
|--|----------------------------|
| <ul style="list-style-type: none"> • STEP 7 Professional (TIA Portal) | Yes |
| <ul style="list-style-type: none"> • STEP 7 | Yes |
| <ul style="list-style-type: none"> • WinCC flexible Advanced 2008 | Yes; Software version: SP5 |
| <ul style="list-style-type: none"> • WinCC Advanced (TIA Portal) | Yes |

• STEP 5

Yes; Optional; software version: STEP 5 V7.23 HF2 (incl. GRAPH 5/II V7.15)

Mechanics/material

Material of housing	metal
Handle	Yes; retractable
Socket for Kensington lock	Yes
rubber corner guards	Yes

Dimensions

Width	385 mm
Height	53 mm
Depth	275 mm

Weights

Weight, approx.	3.4 kg; incl. rechargeable battery
-----------------	------------------------------------

Scope of supply

Accumulator	Yes
Power supply	Yes
Backpack	Yes
SIMATIC Software	Yes
Recovery media	Yes; Restore & Recovery

Other

free hotline	Yes
Note:	Made in Germany: development and production in Germany
last modified:	03/20/2020