

FRONT CONN. MOD.(DIGITAL 1X50 S) S7-1500  
 Front connector module w. 1x50 pole IDC-connect. for digital 32 I/O modules of S7-1500 potential supply via screw terminals



Target system	SIMATIC S7-1500
Suitability for use	Digital I/O modules
Product type designation	Fully modular connection
Product designation	Front connector module

Operating data	
Operating voltage	
• at DC / Rated value	24 V
• rated value	24 V
• at DC / maximum	60 V
Continuous current / at DC / per plug-in contact / maximum	1 A
Total current / maximum	2 A; for mounting position horizontal
Operating temperature	0 ... 60 °C
Ambient temperature	
• during operation	0 ... 60 °C
• during storage	-40 ... +70 °C
Number of poles	40; of the front connector
Manufacturer's article number / of device connector / usable	replacement for S7-1500 40 pole

number of the plug contacts / of the electrical connection	1
Type of electrical connection / for connecting cable	Plug-in connection
Number of poles / at the 1st interface	50; the IDC connector for the connection cable
Position / of the terminal	at the top
Type of electrical connection / for power supply	Screw-type terminal
Number of terminals	4; 4 x 1 x L+
Width of screwdriver blade	3.5 mm
Tightening torque / with screw-type terminals	0.4 ... 0.7 N·m
Product component / required / connection plate	No
Number of cables / per connection	2; Connection for internal system: Combination of 1 or 2 Wires until the sum total of cross sections be achieved in a ferrule.
Wire stripping length	10 mm
Type of connectable conductor cross-sections / solid	No
Connectable conductor cross-section	
<ul style="list-style-type: none"> <li>• for flexible conductor / with core end processing</li> </ul>	0.25 ... 1.5 mm <sup>2</sup> ; End sleeve according to DIN 46228/1 or DIN 46228/4 with plastic collar max. 0.75 mm <sup>2</sup>
<ul style="list-style-type: none"> <li>• stranded</li> </ul>	0.5 ... 2.5 mm <sup>2</sup>
<ul style="list-style-type: none"> <li>• finely stranded / without core end processing</li> </ul>	0.5 ... 2.5 mm <sup>2</sup>
<ul style="list-style-type: none"> <li>• finely stranded / with core end processing</li> </ul>	0.25 ... 1.5 mm <sup>2</sup>
Type of wire end sleeve	
<ul style="list-style-type: none"> <li>• without plastic sleeve / acc. to DIN 46228-1</li> </ul>	Length 10mm
<ul style="list-style-type: none"> <li>• with plastic sleeve / acc. to DIN 46228-4</li> </ul>	Length 10mm
Outer diameter / of the wire insulation	3.1 mm; to the connection of the supply terminal
Wire length / maximum	30 m; between front connector module and terminal module

#### General data

Mounting type	direct mounting
Degree of pollution	2
Overvoltage category	2
Design tested acc. to type of protection / EEx e	No
Certificate of suitability / cULus approval	Yes
Equipment marking / acc. to DIN EN 81346-2	X
Material / of the insulating body	other
Color / of the enclosure	black
Product feature / transparent	No
Net weight	0.099 kg
<b>last modified:</b>	06/27/2017