

S7-300 FRONTCON. W. SINGLE CO. 5.0 M UL
FRONT CONNECTOR FOR SIMATIC S7-300 20-POLE (6ES7392-1AJ00-0AA0) WITH 20 SINGLE CORES AWG 20, SINGLE CORES UL / CSA AWM STYLE 1007/1569 FT2 TR64, SCREW-TYPE
VERSION PACKING UNIT=1 PCS., L = 5.0 M



Figure similar

Target system	SIMATIC S7-300
Product properties, functions, components / general	
Wire length	5 m
Color / of cable sheath	blue
Outer diameter / of cable sheath	2.2 mm
Conductor cross section / Rated value	0.5 mm²
Number of channels	20
Number of poles	20
Operating data	
Operating voltage / at DC	
• Rated value	24 V
• maximum	30 V
Continuous current / with simultaneous load on all cores / at DC / maximum permissible	1.5 A
Ambient temperature	
• during storage	-30 ... +70 °C
• during operation	0 ... 60 °C

General data

Certificate of suitability / cULus approval	No
Suitability for interaction	
• Input card PLC	Yes
• PLC output card	Yes
Suitability for use	
• digital signal transmission	Yes
• analog signal transmission	No
Equipment marking / acc. to DIN EN 81346-2	W
Net weight	1.3 kg