

S7-400 FRONT CONN. W. SINGLE CORES 2.5M  
 FRONT CONNECTOR FOR S7-400 48-POLE (6ES7492-1CL00-0AA0), WITH 46 SINGLE CORES 0.5 MM<sup>2</sup>, H05V-K SINGLE CORES, CRIMP-TYPE VERSION, PACKING UNIT= 1 PCS., L = 2.5 M



Figure similar

Target system	SIMATIC S7-400
---------------	----------------

**Product properties, functions, components / general**

Wire length	2.5 m
Color / of cable sheath	blue
Outer diameter / of cable sheath	2.2 mm
Conductor cross section / Rated value	0.5 mm <sup>2</sup>
Number of channels	46
Number of poles	48

**Operating data**

Operating voltage / at DC	
• Rated value	24 V
• maximum	30 V
Continuous current / with simultaneous load on all cores / at DC / maximum permissible	1 A
Ambient temperature	
• during storage	-30 ... +70 °C
• during operation	0 ... 60 °C

## General data

Certificate of suitability / cULus approval	No
Suitability for interaction	
• Input card PLC	Yes
• PLC output card	Yes
Suitability for use	
• digital signal transmission	Yes
• analog signal transmission	No
Equipment marking / acc. to DIN EN 81346-2	W
Net weight	1.18 kg