

S7-400 FRONT CONN. W.SINGLE COR. 3.2M UL
 FRONT CONNECTOR FOR SIMATIC S7-400 48-POLE (6ES7492-1AL00-0AA0) WITH 46 SINGLE CORES AWG 20, SINGLE CORES UL / CSA AWM STYLE 1007/1569 FT2 TR64 SCREW-TYPE
 VERSION PACKING UNIT=1 PCS., L = 3.2 M



Figure similar

Target system	SIMATIC S7-400
Product properties, functions, components / general	
Wire length	3.2 m
Color / of cable sheath	blue
Outer diameter / of cable sheath	2.2 mm
Conductor cross section / Rated value	0.5 mm ²
Number of channels	46
Number of poles	48
Operating data	
Operating voltage / at DC	
• Rated value	24 V
• maximum	30 V
Continuous current / with simultaneous load on all cores / at DC / maximum permissible	1 A
Ambient temperature	
• during storage	-30 ... +70 °C
• during operation	0 ... 60 °C

General data

Certificate of suitability / cULus approval	No
Suitability for interaction	
• Input card PLC	Yes
• PLC output card	Yes
Suitability for use	
• digital signal transmission	Yes
• analog signal transmission	No
Equipment marking / acc. to DIN EN 81346-2	W
Net weight	1.51 kg