## **SIEMENS**

## Data sheet

6ES7922-5CB00-0HC0

S7-1500 FRONTCON. 40CORES HALOG.-FR 10M FRONT CONN. FOR SIMATIC S7-1500 40PIN(6ES7592-1AM00-0XB0) WITH 40 SINGLE CORES 0.5 MM2 CORE TYPE H05Z-K (HALOGEN-FREE) SCREW-TYPE VERSION L = 10.0M



Product properties, functions, components / general	
Wire length	10 m
Color / of cable sheath	blue
Outer diameter / of cable sheath	2.2 mm
Conductor cross section / Rated value	0.5 mm²
Number of channels	40
Number of poles	40
Operating data	
Operating voltage / at DC	
Rated value	24 V
• maximum	30 V
Continuous current / with simultaneous load on all cores / at DC / maximum permissible	1.5 A
Ambient temperature	
during storage	-15 +60 °C
<ul><li>during operation</li></ul>	0 60 °C
General data	

No

Certificate of suitability / cULus approval

Suitability for interaction	
Input card PLC	Yes
PLC output card	Yes
Suitability for use	
<ul> <li>digital signal transmission</li> </ul>	Yes
<ul> <li>analog signal transmission</li> </ul>	No
Equipment marking / acc. to DIN EN 81346-2	W
Net weight	3.94 kg