



TERM. BL. TPA PUSH-IN TERM. S7-1500

Terminal block TPA 3-tier for analog modules of SIMATIC S7-1500
sort: push-in terminal without LED, pack. unit = 1 piece 16pole IDC
connect. f. cable

Operating data

Operating voltage	
• at DC / Rated value	24 V
• rated value	50 V
• at DC / maximum	50 V
Current / rated value	1 A
Continuous current / at DC / per signal cable / maximum	1 A
Operating temperature	0 ... 60 °C
Ambient temperature	
• during operation	0 ... 60 °C
• during storage	-40 ... +70 °C
Number of terminal levels	1
Number of terminal points / per terminal level	1
Number of terminals	30
Width of screwdriver blade	3.5 mm
Design of terminal / Terminal levels internally linked	No
Product component	
• PE connection	No

• Shield connection	No
• Disconnector	No
• required / connection plate	No
Product feature / Infeed function	Yes
Product feature / cross-connectable	No
Number of cables / per connection	2
Connectable conductor cross-section	
• for flexible conductor / with core end processing	0.2 ... 2.5 mm ²
• stranded	0.2 ... 2.5 mm ²
• finely stranded / without core end processing	0.2 ... 2.5 mm ²
• finely stranded / with core end processing	0.2 ... 2.5 mm ²
Number of poles / at the 1st interface	16
number of the plug contacts / of the electrical connection	1
Wire length / maximum	30 m

General data	
Degree of pollution	2
Overvoltage category	2
Design tested acc. to type of protection / EEx e	No
Certificate of suitability / cULus approval	Yes
Equipment marking / acc. to DIN EN 81346-2	X
Length	76 mm
Height / of the enclosure	76 mm
Width / of the enclosure	57 mm
Depth / of the enclosure	60 mm
Height / with lowest-profile installation	60 mm
Net weight	0.11 kg