



SIMATIC DP, BUS CONNECTOR FOR PROFIBUS UP TO 12 MBIT/S 35 DEGREE ANGLE CABLE OUTLET, IPCD TECHNOLOGY FAST CONNECT, WITHOUT PG SOCKET 15,8 X 54 X 39,5 MM (WXHxD),

Transfer rate

- with PROFIBUS

9.6 kbit/s ... 12 Mbit/s

Interfaces

Number of electrical connections

- for PROFIBUS cables
- for network components and terminal equipment

2

1

Design of the electrical connection / FastConnect

Yes

Mechanical data

material / of the housing

plastic

Design, dimensions and weight

Width

15.8 mm

Height

54 mm

Depth

39.5 mm

Net weight

29 g

Permitted ambient conditions

Ambient temperature

- during operating
- during storage
- during transport

0 ... 60 °C

-40 ... +70 °C

-40 ... +70 °C

Relative humidity

- at 25 °C / without condensation / during operating / maximum

95 %

Protection class IP

IP20

Product properties, functions, components / general

Product feature / [not supplied - silicon-free]

Yes

Composant produit

- PG connection socket
- décharge de traction

No

Yes

Standards, specifications, approvals

Verification of suitability

- RoHS conformity
- UL-registration

Yes

Yes

letzte Änderung:

Jul 17, 2012