



Figure similar

MLFB-Ordering data

6FC5203-0AF05-0AB1

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Screen		Ambient conditions	
Screen diagonal	15.0 in TFT color XGA with LED backlight	Climate class according to EN60721-3-3 Condensation and icing excluded. Low air temperature 0 °C (32 °F).	
Screen resolution	1024 x 768 Pixel		
Rated data		Ambient temperature	
Input voltage	DC 5 V	Operation on the front	0 ... 45 °C (32 ... 113 °F)
	Via PCU or TCU	Operation at the rear	0 ... 55 °C (32 ... 131 °F)
Power consumption		Storage	-20 ... 55 °C (-4 ... 131 °F)
Maximum	25.0 W	Transport	-20 ... 55 °C (-4 ... 131 °F)
Standard	15.0 W	Relative humidity	
Mechanical data		Operation	5 ... 95 %
Net weight	8.4 kg (18.52 lb)	Storage	5 ... 95 %
Width	483.0 mm (19.02 in)	Transport	5 ... 95 %
Height	355.0 mm (13.98 in)	Approvals	
Depth	53.0 mm (2.09 in)	Certificate of suitability	CE / cULus
	Without USB protective cover on the front		
Installation depth	42.0 mm (1.65 in)		
with PCU 50	127.0 mm (5.00 in)		
	Clearance + 10 mm (0.39 in)		
Mounting surface			
Cutout width	450.0 mm (17.72 in)		
Cutout height	335.0 mm (13.19 in)		
Degree of protection			
Front side	IP65		
Rear side	IP00		