

## **Data sheet for SINUMERIK Operator panel front TP 015AT**

MLFB-Ordering data 6FC5203-0AF08-1AB3



Figure similar

Client order no. : Item no. :
Order no. : Consignment no. :
Offer no. : Project :
Remarks :

Screen		Ambient conditions	
Screen diagonal	15.0 in TFT color XGA		
Screen resolution	1024 x 768 Pixel	Climate class according to EN60721-3-3	Condensation and icing excluded. Low air temperature 0 °C (32 °F).
	Rated data		
Input voltage	DC 24 V	Ambient temperature	
		Operation on the front	0 45 °C (32 113 °F)
		Operation at the rear	0 55 °C (32 131 °F)
Power consumption		Storage	-20 55 °C (-4 131 °F)
Maximum	50.0 W	Transport	-20 55 °C (-4 131 °F)
Standard	24.0 W	Relative humidity	
Mechanical data		Operation	5 95 %
Net weight	7.6 kg (16.76 lb)	Storage	5 95 %
Width	483.0 mm (19.02 in)	Transport	5 95 %
Height	355.0 mm (13.98 in)	Approvals	
Depth	53.0 mm (2.09 in) Without USB protective cover on the front	Certificate of suitability	CE / cULus
Installation depth	42.0 mm (1.65 in)		
	Clearance + 10 mm (0.39 in)		
Mounting surface			
Cutout width	450.0 mm (17.72 in)		
Cutout height	335.0 mm (13.19 in)		
Degree of protection			
Front side	IP65		
Rear side	IP00		