



Figure similar

### MLFB-Ordering data

6FC5303-0AF23-1AA1

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

| Rated data              |                                         | Ambient conditions                                                                                           |                                |
|-------------------------|-----------------------------------------|--------------------------------------------------------------------------------------------------------------|--------------------------------|
| Input voltage           | DC 24 V                                 | Climate class according to EN60721-3-3    Condensation and icing excluded. Low air temperature 0 °C (32 °F). |                                |
| Power consumption, max. | 21.2 W                                  |                                                                                                              |                                |
| Mechanical data         |                                         | Ambient temperature                                                                                          |                                |
| Net weight              | 1.200 kg (2.65 lb)                      | Operation on the front                                                                                       | 0 ... 45 °C (32 ... 113 °F)    |
| Width                   | 310.0 mm (12.20 in)                     | Operation at the rear                                                                                        | 0 ... 55 °C (32 ... 131 °F)    |
| Height                  | 175.0 mm (6.89 in)                      | Transport                                                                                                    | -40 ... 70 °C (-40 ... 158 °F) |
| Depth                   | 85.2 mm (3.35 in)                       | Storage                                                                                                      | -25 ... 55 °C (-13 ... 131 °F) |
|                         | With connector for handwheel connection | Relative humidity                                                                                            |                                |
| Installation depth      | 53.9 mm (2.12 in)                       | Operation                                                                                                    | 5 ... 95 %                     |
|                         | With connector for handwheel connection | Storage                                                                                                      | 5 ... 95 %                     |
| Mounting surface        |                                         | Transport                                                                                                    | 5 ... 95 %                     |
| Cutout width            | 285.0 mm (11.22 in)                     | Approvals                                                                                                    |                                |
| Cutout height           | 155.0 mm (6.10 in)                      | Certificate of suitability                                                                                   | CE, cULus                      |
| Degree of protection    |                                         |                                                                                                              |                                |
| Rear side               | IP00                                    |                                                                                                              |                                |
| Front side              | IP65                                    |                                                                                                              |                                |
|                         | Key-operated switch IP54                |                                                                                                              |                                |